



BOLL EPOXY PRIMER IN SPRAY

The product is a single-component substance used to conserve and protect various types of metal surfaces. With the special epoxy resins applied, it is ideal to be applied directly onto metal sheets, aluminium, galvanised steel and old lacquer coats. With its insulating properties, it adheres well to surfaces and has high anticorrosion properties. It dries fast, it is easy to handle and has good filling properties. It can be covered with most paints and lacquers.

Application:

Carefully clean and degrease and dry the place to be covered with paint. Cover the adjacent surfaces with paper. Before use, shake the container well for about 3 minutes. Keep the container at a distance of 15-20 cm from the painted surface. After use, turn over the container and spray until the valve is empty. Drying time: about 30 minutes at 20 °C

Physical properties:

base:	epoxy resin, pigments, fillers, zinc phosphate	
colour:	grey	
Density:	0.901 g / ml	
Solids:	about 28%	
Polyvinyl chloride:	about 38%	
Drying time:	depends on coat thickness, temperature and ventilation	
Indications:	Dust dryness	about 40 min
	Grinding	about 8 hours
	Coating (with the same products)	after about 8 hours
	Coating (with another product)	after about 12 hours

Comments:

All technical specifications are approximate. We recommend to test the material to make sure it is appropriate for the specific application. The producer reserves the right to improve the product and change its technical properties, including modifications to the specification.