



**BOLL**

*Permanenem kováčsko auto!*

## **BOLL ANTI – GRAVEL 1L**

The car body protective agent is based on synthetic resins. It develops an elastic coat which provides an ideal protection against hits by stones and mechanical factors. It is applied to protect thresholds, bumpers, spoilers and other elements of car body. The product is highly resistant to abrasion (against hits by stones). It can be painted with all lacquer systems.

### **Application:**

The car body protective agent can be easily applied with pneumatic spray guns. Carefully clean and degrease and dry the place to be covered. Cover the adjacent surfaces with paper. Before use, shake the container well for about 3 minutes. The best results are obtained at the pressure of 4 to 6 atmospheres.

Optimum coat thickness: about 1 mm. Clean the gun with mineral spirits after use.

Do not spray on elements of the exhaust system, engine, gearbox and suspension. The surface can be lacquered after about 3 hours. In case of water lacquers – after about 24 hours.

### **Physical properties:**

Colour:	white/grey/black
density (at 20°C):	1.04 g/cm <sup>3</sup>
boiling temperature:	78°C
flash point:	0°C
ignition temperature:	200°C
self-ignition:	it does not self-ignite
explosive limit:	upper: 7.7 % vol. / lower: 0.8 % vol.

### **Comments:**

*All technical specifications are approximate. We recommend to test the material to make sure it is appropriate for the specific application. The producer reserves the right to improve the product and change its technical properties, including modifications to the specification.*