



## THERMAL LACQUER 650°C SPRAY



EAN code: 5907588400008 item no.: 001018 silver

EAN code: 5907588410021 item no.: 001019 black



### PROPERTIES

Thermal spray paint is a fast drying paint that is ideal for painting all parts exposed to high temperatures in the field of motor vehicles, motorcycles, etc.



### COLOUR

 silver black

### METHOD OF USE

Thoroughly clean, degrease and dry the area to be painted. Cover adhering surfaces with paper. Shake the container well for about 3 minutes before use. While painting, keep the container at a distance of 15-20 cm from the surface to be painted. After use, invert the container and spray until the valve is empty. Drying time: approx. 60 minutes at 20°C. After annealing at 200°C for approx. 10 minutes the coating becomes resistant to petrol, solvents and degreasers.



### APPLICATION



Thoroughly clean and degrease the surface



Shake thoroughly




Spray 2-3 layers from a distance of about 15-20 cm



Flash-off time between layer: 5 ÷ 10 minutes



Drying time: 60 minutes



Spray until the valve is empty



## PHYSICAL PROPERTIES

boiling point:	-45°C
flash point:	< 0°C
density at 20°C:	0,720 g/cm <sup>3</sup>
flammability limit:	upper: 13,0 % vol. / lower: 0,7 % vol.



## STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



## SHELF LIFE

24 months from the date of production placed on the package.



## SAFETY

See Safety Data Sheet.



## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.