UNDERBODY BRUSHABLE

EAN code: 5907588400343 item no.: 001032 con. 1kg
EAN code: 5907588400350 item no.: 001033 con. 2kg
EAN code: 5907588400367 item no.: 001034 con. 4kg

PROPERTIES

This bitumen rubber-based underbody preservative forms a flexible film that perfectly protects the underbody of your car against stone chips, salt, water and mechanical influences. It is resistant to gritting salt and industrial fumes. It also acts as a sound absorber.

COLOUR

black

METHOD OF USE

The underbody preservative can be easily applied with a brush. Thoroughly clean and degrease and then dry the areas to be conserved. After 24 hours the maintained vehicle is fit for use.

SURFACE

- **two-component acrylic primer -** apply varnish or control powder. After sanding, blow off, degrease with "BOLL silicone remover" and then apply another coat.

- **epoxy primer -** can be used to isolate materials. After sanding, blow off, degrease with "BOLL silicone remover" and then apply another coat.

- **polyester putties -** sand, blow off and degrease with "BOLL Silicone remover" and then apply the next coat.

INFORMATION

Do not spray toward engine, transmission, brake parts or exhaust system. CAN BE VARNISHED.

APPLICATION

Thoroughly clean and mat the surface

Thoroughly clean and degrease the surface

For corroded surfaces, we suggest using BOLL rust neutralizer or BOLL anticorrosive paint.

Mix thoroughly

Apply evenly with a brush

Recommended coating thickness 2-4 mm

Drying time: approx. 5-7 hours at temp. 20°C
After 24 hours the preserved vehicle is fit for use

PHYSICAL PROPERTIES

density (at 20°C):	1,04 g/cm^3
boiling point:	142°C
flashpoint:	21-55°C
flash point:	450°C
flammability limits:	upper: 7,5 % vol. / lower: 0,6 % vol.

EQUIPMENT CLEANING

Wash the brush with nitrocellulose solvent (Nitro) or white spirit.

STORAGE CONDITIONS

Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

SHELF LIFE

Two years from the date of production on the packaging.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.