



## PREFILL SPRAY



EAN code: 5907588400374 item no.: 001028 female

EAN code: 5907588403627 item no.: 0010281 PROFI female

EAN code: 5907588407830 item no.: 0010282 PROFI PLUS female

## + PROPERTIES

The prefill spray is filled with gas and is ready for use after adding the colour of the corresponding shade. The 400 ml can can hold up to 100 ml of colour with a viscosity of up to 240s (DIN4/20°C). It can be used almost any type of paint. Dilutes acrylic, alkyd and cellulose paints very well. Product performance 1-2m<sup>2</sup> depending on the layer thickness. The drying time depends on the type of paint used.

**NOTE: The product is intended for single-component media. Apply acrylic paint through a sieve.**

## METHOD OF USE

Thoroughly clean and degrease, and then dry the places to be covered with paint. Cover adjoining surfaces with paper. Before use, shake the container well for about 3 minutes. When painting, keep the container 15-20 cm from the surface to be coated. After use, invert the container and spray until the valve is empty.

**Important:** after filling the can with thick varnish, rinse the valve with 10 ml of solvent in the same way as when filling with varnish. Use a solvent in accordance with the recipe of a given mixing plant.

## PHYSICAL PROPERTIES

boiling point:	-24°C
autoignition temperature:	235°C
flash point:	< 0°C
density at 20°C:	0,722 g/cm <sup>3</sup>
flammability limit:	upper: 18,6 % vol. / lower: 2,6 % vol.

## STORAGE



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

## SHELF LIFE

24 months from the date of production placed on the package.



## SAFETY

See Safety Data Sheet



## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.