

PLASTIC FINELINE TAPE



EAN code: 5907588400893 item no.: 004013 type 3mm/55m EAN code: 5907588400916 item no.: 0040131 type 6mm/55m EAN code: 5907588400923 item no.: 0040132 type 9mm/55m EAN code: 5907588400930 item no.: 0040133 type 12mm/55m



PROPERTIES

The tape is perfect for helping in paint jobs when painting various oval shapes, cutting off elements, etc. It adheres well to a variety of surfaces and leaves no residue after the drying process. Solvent resistant.



COLOUR



green



METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dry, dust-free and degreased. When applying the tape, apply maximum pressure to ensure adequate adhesion.



PHYSICAL PROPERTIES

Carrier: heat-stabilized, cadmium-free film

Thickness: 0,10 mm
Total thickness: 0,13 mm

Adhesive base: modified rubber
Peel strength: 5,0 N/25 mm
Tensile strength: 60 N/25 mm

Elongation (yield point): 150%

Temperature resistance: from 30 to +130°C

Resistance to UV radiation: limited Weather resistance: limited Core diameter: 76 mm



PRZECHOWYWANIE







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

PLASTIC FINELINE TAPE Page - 1



TERMIN PRZYDATNOŚCI

The varnish tape stored in a dry place at 18 ° C and 55% relative humidity retains its properties for 12 months.



UWAGI

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

PLASTIC FINELINE TAPE Page - 2