

STRUCTURE LACQUER FOR PLASTIC SPRAY

EAN code: 5907588403191 item no.: 0014001 grey EAN code: 5907588402446 item no.: 001400 black



COLOUR			
	grey	black	

METHOD OF USE

Thoroughly clean and degrease the area to be painted. Cover adhering surfaces with paper. Shake the container well for about 3 minutes before use. While painting, keep the container at a distance of 15-20 cm from the surface to be painted. After use, invert the container and spray until the valve is empty. After approx. 20 minutes the structure can be varnished.

APPLICATION

	Thoroughly clean and degrease the surface
3min.	Shake thoroughly
15-20 (m) 2-3x	Spray 2-3 layers from a distance of about 15-20 cm
	Flash-off time between layer: 5 ÷ 10 minutes
	After approx. 20 minutes the structure can be varnished.
	Spray until the valve is empty

PHYSICAL PROPERTIES

boiling point: autoignition temperature: flash point: vapor pressure at 20°C: density at 20°C: flammability limit: organic solvents:	-24°C 235°C -42°C 4,3 bar 0,843 g/cm ³ upper: 18,6 % vol. / lower: 1,1 % vol. 72.8 %
organic solvents:	73,8 %

STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

SHELF LIFE

24 months from the date of production placed on the package.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.