

SILICON SPRAY



EAN code: 5907588402576 item no.: 001022 cap. 200ml EAN code: 5907588402576 item no.: 001023 cap. 400ml



PROPERTIES

Silicone spray is used to lubricate door locks, rubber seals, chains, hinges, etc. It is excellent for protecting rubber parts from drying, freezing, sticking and makes them more flexible. It is resistant to high and low temperatures and water.



COLOUR

colorless



METHOD OF USE

Thoroughly clean, degrease and dry the area to be lubricated. Shake the container for about 3 minutes before use. Apply a thin layer of silicone evenly. For hard-to-reach areas, use the spray tube. During freezing weather, spray the rubber seals of the doors, trunk and hood thoroughly before each car wash. After use, invert the container and spray until the valve is empty.



APPLICATION



Thoroughly clean the surface and degrease it



Mix thoroughly



Apply a thin layer of silicone



After use, invert the container and spray until the valve is empty

SILICON SPRAY Page - 1



PHYSICAL PROPERTIES

density at 20°C: 0,653 g/cm³



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

SILICON SPRAY Page - 2