

MASKING TAPE 80°C



EAN code: 5907588402651 item no.: 004001 type 19mm/50m EAN code: 5907588402668 item no.: 004002 type 25mm/50m EAN code: 5907588402675 item no.: 004003 type 30mm/50m EAN code: 5907588402682 item no.: 004004 type 38mm/50m EAN code: 5907588402699 item no.: 004005 type 50mm/50m



PROPERTIES

High quality paper tape for paint jobs. It adheres well to a variety of surfaces and leaves no residue after the drying process.

Available in rolls of 50 m in length and widths: 19, 25, 30, 38 and 50 mm



COLOUR





METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dust-free and degreased.



PHYSICAL PROPERTIES

description: heat resistant paper masking tape, saturated crepe paper

binder : natural rubber

 $\begin{array}{ll} total\ thickness: & 137\ \mu m \\ adhesion\ to\ steel: & 6.\ 5\ N/25\ mm \\ tensile\ strength: & 100\ N/25\ mm \end{array}$

total elongation : 9,5
ROLLING BALL TACK test : 1cm



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

MASKING TAPE 80°C Page - 1



SHELF LIFE

Stored in a dry place at 18 - 21°C, the tape retains its properties for 12 months.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

MASKING TAPE 80°C Page - 2