

WHITE GREASE - SPRAY



EAN code: 5907588402774 item no.: 001036 cap. 400ml



PROPERTIES

White grease is a lithium-teflon based product designed to protect components exposed to particularly high loads. Protects moving parts, guides as well as bearings, pins and battery terminals. Acts as a friction minimizer, insulator and preservative. Protects against the effects of water, salt, rust as well as low and high temperatures. Causes longer life of bearings, hinges, locks, chains, gears, etc.



COLOUR



white



METHOD OF USE

Application range -20°C to +150°C. Shake the container well for approx. 3 minutes before use. Clean the area to be lubricated thoroughly and apply the grease evenly in a thin layer from a distance of approx. 5-10 cm.



NOTES

Do not apply to varnished wires and electrical windings - the product dissolves resins.



APPLICATION



Mix thoroughly



Apply a thin layer of grease evenly



PHYSICAL PROPERTIES

physical state: aerosol density at 20°C: 0,689 g/cm³

WHITE GREASE – SPRAY Page - 1



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

WHITE GREASE – SPRAY Page - 2