

TECHNICAL DATA SHEET

ZINK + ALUMINIUM SPRAY


EAN code: 5907588402798 item no.: 0010212 silver



+ PROPERTIES

Zinc + Aluminum Spray is a fast-drying agent that provides excellent corrosion protection for all metal parts and structures. It is used to protect and repair damaged galvanized parts, welded and cut areas. The aluminum admixture provides excellent and aesthetic corrosion protection. It has excellent adhesion to most metal surfaces. Resistant to temperatures up to 120°C. After drying, it can be painted.

COLOUR



silver

APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with "BOLL Silicon remover"



Mix thoroughly



Numbers of layers: 1 – 2
distance 15 – 20 cm



Time between layers: 5 – 10 minut



Drying time 24 hours



After use, turn the container over and spray until the valve is empty

**PHYSICAL PROPERTIES**

Physical state:	aerosol
Zinc content by weight in dry matter:	25%
Aluminum content by weight in dry matter:	20%
Temperature of application:	+15°C – +25°C

**STORAGE**

Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

**SHELF LIFE**

Two years from the production date placed on the package.

**SAFETY**

See Safety Data Sheet.

**OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.