

**ZINK + ALUMINIUM SPRAY**

EAN code: 5907588402798 item no.: 0010212 silver

**PROPERTIES**

Zinc + aluminium spray is a fast-drying agent, providing excellent anticorrosive protection to all metal parts and structures. It is used to protect and repair damaged galvanized, welded and cut elements. The addition of aluminium provides excellent anticorrosive protection and aesthetic value. It has excellent adhesion to most metal surfaces. Temperature resistant up to 120°C. Can be painted after drying.

**COLOUR**

silver

**METHOD OF USE**

Clean, degrease and then sand the metal surface smoothly. Shake the container for about 3 minutes before use. Spray from a distance of about 15-20 cm, thoroughly covering the component. After 15-20 minutes the layer is touch resistant. Total drying time: 24 hours. Optimum use temperature: 16-25°C. After use, invert the container and spray until the valve is empty.

**SUBSTRATE**

- **metal** - sand, blow and degrease with "BOLL silicone remover", then apply the next coat.

- **non-ferrous metals (zinc, aluminium, copper, etc.)** - sand, blow and degrease with "BOLL Silicone remover", then apply the next coat.

- **paint coatings** - sand, blow, degrease with "BOLL Silicone remover", then apply the next coat.



APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface



Shake thoroughly



Spray 1-2 layers from a distance of about 15-20 cm



Flash-off time between layers: 5 ÷ 10 minutes



Drying time: 24 hours



Spray until the valve is empty



PHYSICAL PROPERTIES

density at 20°C:	0,826 g/cm ³
zinc content by weight in dry matter:	25%
aluminium content by weight in dry matter:	20%



STORAGE CONDITION



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.