



ACRYLIC CLEAR LACQUER RALLY SPRAY



EAN code: 5907588406079 item no.: 0010127 colourless

+ PROPERTIES

Clear coat is a fast-drying and damage-resistant acrylic spray lacquer with excellent adhesion and high gloss. Can be used on surfaces such as metal, wood and many types of hard plastics and newly painted surfaces.

• COLOUR

colourless

☞ METHOD OF USE

When applying the varnish to a surface that has not been previously cleaned and prepared, remove all contaminants from the surface and then degrease and dry. Cover adjacent areas. The contents of the can should be at room temperature. Shake the container for about 3 minutes before use. Test the spray on a test surface. Apply crosswise from a distance of 15-20 cm creating several layers. After use, invert the container and spray until the valve is empty. The top coat can be polished after 24 hours. Drying time: 1h at 20°C.

↓ APPLICATION



Thoroughly clean and degrease the surface



Shake thoroughly



Spray 1-2 layers from a distance of about 15-20 cm



Flash-off time between layer: 5 ÷ 10 minutes



Drying time: 1 hour



Spray until the valve is empty



PHYSICAL PROPERTIES

boiling point:	-44°C
autoignition temperature:	340°C
flash point:	-97°C
density at 20°C:	0,702 g/cm ³
flammability limit:	upper: 13,0 % vol. / lower: 1,5 % vol.



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.