

CERAMIC SPRAY



EAN code: 5907588402859 item no.: 001040 cap. 400ml



PROPERTIES

Ceramic spray is a lubricant with ceramic additive which is resistant to high temperatures (up to 1400°C). It is used to lubricate screws and similar joints in areas particularly exposed to high temperatures. Excellent for lubrication of ABS braking systems. It perfectly protects aluminium elements and acts as an anti-corrosion agent. Resistant to water and salt.



COLOUR



metallic



METHOD OF USE

Shake the container vigorously for about 3 minutes before use. Apply a thin, even layer from a distance of about 15 cm.



APPLICATION



Mix thoroughly



Apply a thin layer of grease evenly



PHYSICAL PROPERTIES

physical state: aerosol density at 20°C: 0,658 g/cm³

CERAMIC SPRAY Page - 1



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

CERAMIC SPRAY Page - 2