

TECHNICAL DATA SHEET

ANTI-SPATTER SPRAY FOR WELDING

EAN code: 5907588402873 item no.: 001042 cap. 400ml



+ PROPERTIES

Welding protection spray is a high-quality oil and solvent-based product for the maintenance and protection of welding torches. It keeps the welding nozzle clean and ensures that weld spatters do not stick to the discharge nozzle and work surface, while not reducing the quality of the weld. Very efficient in use. Subsequent bronzing, galvanizing, anodizing or painting is possible without special cleaning. Only if excessive amounts are used, cleaning with a cleaner and degreaser may be necessary before post-treatment.

• COLOUR

colourless

⤿ METHOD OF USE

Spray on the welding tips from a distance of about 15 cm. To protect the surface to be treated, hold the can at a distance of 30 cm and also apply the spray to the surface on both sides from the weld to be welded. Start the welding process in cavities and narrow spaces only after the solvent has evaporated.

/// APPLICATION



Mix thoroughly



Apply from a distance of 15 - 20 cm

+ PHYSICAL PROPERTIES

Physical state:	aerosol
Temperature of use:	+10°C – +35°C

**STORAGE**

Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

**SHELF LIFE**

Two years from the production date placed on the package.

**SAFETY**

See Safety Data Sheet.

**OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.