



**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE
Other means of identification:
UFI: 37YV-E0W8-S00S-HKPN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses (Professional users): Agent for protecting profiled surfaces.
Relevant uses (Industrial user): Agent for protecting profiled surfaces.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
"BOLL" Wojciech Dalewski Spółka Jawna
ul. Chemiczna 3
65-713 Zielona Góra - Polska
Phone: 68 451 99 99 - Fax: 68 451 99 00
huszcza@boll.pl
<https://www.boll.pl>
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning
 
Hazard statements:
H226 - Flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260: Do not breathe vapours
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/eye protection.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
Supplementary information:
EUH066: Repeated exposure may cause skin dryness or cracking.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

BOLL**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 2: HAZARDS IDENTIFICATION ** (continued)****Substances that contribute to the classification**

Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics; Hydrocarbons, C9, aromatics

UFI: 37YV-E0W8-S00S-HKPN**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

*** Changes with regards to the previous version***SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ******3.1 Substance:**

Not relevant

3.2 Mixture:**Chemical description:** a mixture of organic and auxiliary substances**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: Not relevant EC: 919-857-5 Index: Not relevant REACH: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics⁽¹⁾	Self-classified	25 - <50%
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	
CAS: 128601-23-0 EC: 918-668-5 Index: Not relevant REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics⁽¹⁾	Self-classified	2.5 - <10%
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	
CAS: Not relevant EC: 918-481-9 Index: Not relevant REACH: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾	Self-classified	2.5 - <10%
	Regulation 1272/2008	Asp. Tox. 1: H304; EUH066 - Danger	
CAS: 1305-62-0 EC: 215-137-3 Index: Not relevant REACH: 01-2119475151-45-XXXX	Calcium dihydroxide⁽¹⁾	Self-classified	1 - <2.5%
	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

*** Changes with regards to the previous version***SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

- CONTINUED ON NEXT PAGE -

**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 4: FIRST AID MEASURES (continued)**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not available

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

- CONTINUED ON NEXT PAGE -

**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	IOELV (8h)		1 mg/m ³
	IOELV (STEL)		4 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	150 mg/m ³	Not relevant
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	4 mg/m ³	Not relevant	1 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	11 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	11 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	32 mg/m ³	Not relevant
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	4 mg/m ³	Not relevant	1 mg/m ³



PNEC:

Identification				
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	STP	3 mg/L	Fresh water	0,49 mg/L
	Soil	1080 mg/kg	Marine water	0,32 mg/L
	Intermittent	0,49 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant



8.2 Exposure controls:
A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	60,1 % weight
V.O.C. density at 20 °C:	501,3 kg/m ³ (501,3 g/L)
Average carbon number:	10,14
Average molecular weight:	139,97 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not available *

*Not available due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)
Volatility:

Boiling point at atmospheric pressure:	165 - 181 °C
Vapour pressure at 20 °C:	100 Pa
Vapour pressure at 50 °C:	Not available *
Evaporation rate at 20 °C:	Not available *

Product description:

Density at 20 °C:	813 - 834 kg/m ³
Relative density at 20 °C:	0,813 - 0,834
Dynamic viscosity at 20 °C:	Not available *
Kinematic viscosity at 20 °C:	Not available *
Kinematic viscosity at 40 °C:	≥20,5 mm ² /s
Concentration:	Not available *
pH:	Not available *
Vapour density at 20 °C:	Not available *
Partition coefficient n-octanol/water 20 °C:	Not available *
Solubility in water at 20 °C:	Not available *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not available *
Melting point/freezing point:	Not available *

Flammability:

Flash Point:	38 °C
Flammability (solid, gas):	Not available *
Autoignition temperature:	233 °C
Lower flammability limit:	0,6 % Volume
Upper flammability limit:	7,5 % Volume

Particle characteristics:

Median equivalent diameter:	Not available *
-----------------------------	-----------------

9.2 Other information:
Information with regard to physical hazard classes:

Explosive properties:	Not available *
Oxidising properties:	Not available *
Corrosive to metals:	Not available *
Heat of combustion:	Not available *
Aerosols-total percentage (by mass) of flammable components:	Not available *

Other safety characteristics:

Surface tension at 20 °C:	Not available *
Refraction index:	Not available *

*Not available due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY
10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

- CONTINUED ON NEXT PAGE -

**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 10: STABILITY AND REACTIVITY (continued)**

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Avoid direct impact	Risk of combustion	Avoid direct impact	Avoid direct impact

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Can react violently	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION ****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3); Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Not relevant EC: 919-857-5	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LD50 oral	>3492 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Not relevant EC: 918-481-9	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rat
	LC50 inhalation vapour	>20 mg/L	
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation dust	>5 mg/L	

11.2 Information on other hazards:
Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

**** Changes with regards to the previous version**

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:
Acute toxicity:

Identification	Concentration	Species	Genus
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
Calcium dihydroxide CAS: 1305-62-0 EC: 215-137-3	LC50 50,6 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 49,1 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 184,57 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

**** Changes with regards to the previous version**

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Concentration		Species	Genus
Calcium dihydroxide	NOEC	Not relevant		
CAS: 1305-62-0 EC: 215-137-3	NOEC	32 mg/L	Crangon septemspinosa	Crustacean

12.2 Persistence and degradability:
Substance-specific information:

Identification	Degradability		Biodegradability	
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics	BOD5	Not relevant	Concentration	Not relevant
CAS: Not relevant	COD	Not relevant	Period	28 days
EC: 919-857-5	BOD5/COD	Not relevant	% Biodegradable	80 %

12.3 Bioaccumulative potential:

Not relevant

12.4 Mobility in soil:

Not relevant

Insoluble in water

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

*** Changes with regards to the previous version*
SECTION 13: DISPOSAL CONSIDERATIONS
13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION **
Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE
SECTION 14: TRANSPORT INFORMATION ** (continued)


- 14.1 UN number or ID number:** UN1139
- 14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: Not relevant
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1139
- 14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 955
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



- 14.1 UN number or ID number:** UN1139
- 14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: *Calcium dihydroxide (1305-62-0) - PT: (2,3)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: *Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics (Not relevant)*
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION ****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
 - Calcium dihydroxide (1305-62-0)
 - Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
 - Hydrocarbons, C9, aromatics (128601-23-0)
 - Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics
- Removed substances
 - Paraffin waxes and Hydrocarbon waxes (8002-74-2)
 - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (64742-82-1)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements
- Precautionary statements

TRANSPORT INFORMATION (SECTION 14):

- UN number

Texts of the legislative phrases mentioned in section 2:

H226: Flammable liquid and vapour.
 H319: Causes serious eye irritation.
 H336: May cause drowsiness or dizziness.
 H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH BIAŁY - CAVITY WAX - WHITE****SECTION 16: OTHER INFORMATION ** (continued)**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -