



INSIDE COATING SPRAY

EAN code: 5907588402972 item no.: 0010102 white
EAN code: 5907588470018 item no.: 001010 amber

**+** PROPERTIES

The preservative for closed profiles (such as doors, bonnet, thresholds, etc.) is a wax-based agent which forms a flexible protective layer perfectly protecting against water, salt and rust. It is very efficient, transparent in an amber shade after use.

••• COLOUR

white



amber

↪ METHOD OF USE


The agent should be injected into existing holes in the car body using a hose which is included in the set. If necessary, drill holes 6 mm in diameter. Shake the container well for about 3 minutes before use. After use, invert the container and spray until the valve is empty.

↓ APPLICATION

Mix thoroughly



Apply to existing openings in the car body with a hose



Recommended coating thicknesses from 0.2mm to 0.4mm



Drying time approx. 4-5 hours at 20°C



After use, invert the container and spray until the valve is empty



PHYSICAL PROPERTIES

density (at 20°C):	0,66 g/cm ³
boiling point:	- 44°C
flash point:	200°C
flash point:	< 0°C
flammability limits:	upper: 10,9 vol%. / lower: 0,6 % vol.



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

Two years from the date of production on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.