


INSIDE COATING SPRAY





The preservative for closed profiles (such as doors, bonnet, thresholds, etc.) is a wax-based agent which forms a flexible layer protecting against water, salt and rust. It is very efficient, semi-transparent in white or amber shade.

O white	amber	

METHOD OF USE

Inside coating spray should be injected into existing holes in the car body using a tube included in the set. You can drill additional 6 mm diameter holes, If necessary. Shake the container well for about 3 minutes before use. After use, invert the container and spray until the valve is empty.


Amin 1	Mix thoroughly	
	Apply to existing holes in the car body with the attached tube	
	Recommended coating thicknesses from 0. 2mm to 0. 4mm	
	Drying time approx. 4-5 hours at 20°C	
	After use, invert the container and spray until the valve is empty	

PHYSICAL PROPERTIES

physical state: density (at 20°C):

aerosol 0,667 g/cm³

STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

SHELF LIFE

Two years from the production date on the packaging.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.