

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Primer for the paint applied to plastics. In the aerosol.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna

ul. Chemiczna 3

65-713 Zielona Góra - Polska

Phone.: 68 451 99 99 - Fax: 68 451 99 00

technolog@boll.pl

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222

Aerosol 1: Pressurised container: May burst if heated., H229

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity if swallowed, repeated exposure, Category 2, H373

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger









Hazard statements:

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER/doctor if you feel unwell.

P403: Store in a well-ventilated place.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane; Reaction mass of ethylbenzene and xylene

Additional labeling:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: active ingredient mixture with a propellant. Extruding gas: dimethyl ether

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	115-10-6	dimethyl ether(1)	ATP CLP00	
EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37- XXXX		Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	25 - <50 %
CAS:	Non-applicable	Hydrocarbons, C6-C7	, n-alkanes, isoalkanes, cyclics, <5% n-hexane(1) Self-classified	
EC: 921-024-6 Index: Non-applicable REACH: 01-2119475514-35- XXXX		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	25 - <50 %
CAS:	Non-applicable	Hydrocarbons, C6-C7	, isoalkanes, cyclics, <5% n-hexane(1) Self-classified	
EC: 926-605-8 Index: Non-applicable REACH: 01-2119486291-36- XXXX		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	10 - <25 %
CAS: Non-applicable		Reaction mass of eth	ylbenzene and xylene(1) Self-classified	
Index:	EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	10 - <25 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

^{**} Changes with regards to the previous version



This SDS is an English translation of Regulation (EU) $n^{\rm 0}$ 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification			
CAS:	100-41-4	Ethylbenzene(1)	ATP ATP06			
EC: Index: REACH:	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	0,1 - <1 %		
CAS:	108-90-7	Chlorobenzene(1)	ATP ATP09			
EC: Index: REACH:	203-628-5 602-033-00-1 01-2119432722-45- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	0,1 - <0,25 %		

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 3/14



This SDS is an English translation of Regulation (EU) $n^{\rm 0}$ 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) **Page 4/14**



This SDS is an English translation of Regulation (EU) n^{o} 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

(25) 2015/1051						
	Identification	Occupational exposure limits				
dimethyl ether		IOELV (8h)	1000 ppm	1920 mg/m ³		
CAS: 115-10-6	EC: 204-065-8	IOELV (STEL)				
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m ³		
CAS: 100-41-4	EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³		
Chlorobenzene		IOELV (8h)	5 ppm	23 mg/m ³		
CAS: 108-90-7	EC: 203-628-5	IOELV (STEL)	15 ppm	70 mg/m ³		

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	1894 mg/m ³	Non-applicable
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	773 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	2035 mg/m ³	Non-applicable
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	13964 mg/kg	Non-applicable
EC: 926-605-8	Inhalation	Non-applicable	Non-applicable	5306 mg/m ³	Non-applicable
Reaction mass of ethylbenzene and xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 905-588-0	Inhalation	442 mg/m³	442 mg/m ³	221 mg/m³	221 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m³	Non-applicable
Chlorobenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-90-7	Dermal	15 mg/kg	Non-applicable	5 mg/kg	Non-applicable
EC: 203-628-5	Inhalation	70 mg/m ³	Non-applicable	23 mg/m ³	Non-applicable

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	471 mg/m³	Non-applicable
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	608 mg/m ³	Non-applicable
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	1301 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	1377 mg/kg	Non-applicable
EC: 926-605-8	Inhalation	Non-applicable	Non-applicable	1131 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 5/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 905-588-0	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Chlorobenzene	Oral	3 mg/kg	Non-applicable	3 mg/kg	Non-applicable
CAS: 108-90-7	Dermal	3 mg/kg	Non-applicable	3 mg/kg	Non-applicable
EC: 203-628-5	Inhalation	1 mg/m³	Non-applicable	1 mg/m³	Non-applicable

PNEC:

Identification				
dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
Reaction mass of ethylbenzene and xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: Non-applicable	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 905-588-0	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Chlorobenzene	STP	1,4 mg/L	Fresh water	0,032 mg/L
CAS: 108-90-7	Soil	0,166 mg/kg	Marine water	0,003 mg/L
EC: 203-628-5	Intermittent	Non-applicable	Sediment (Fresh water)	0,922 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	0,092 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) **Page 6/14**



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2013 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
= +	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	⊢	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 98,19 % weight

V.O.C. density at 20 °C: 713,9 kg/m³ (713,9 g/L)

Average carbon number: 6,96

Average molecular weight: 96,35 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 713,9 kg/m³ (713,9 g/L)

EU limit for the product (Cat. B.E): 840 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Codour:

Characteristic

Characteristic

Characteristic

Characteristic

Non-applicable *

Volatility:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 7/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Boiling point at atmospheric pressure: -25 °C (Propellant)

Vapour pressure at 20 °C: 399967 Pa

Vapour pressure at 50 °C: Non-applicable *
Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 727 kg/m³
Relative density at 20 °C: 0,727

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Vapour density at 20 °C:

Non-applicable *

Partition coefficient n-octanol/water 20 °C:

Non-applicable *

Solubility in water at 20 °C:

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Recipient pressure:

Explosive properties:

Oxidising properties:

Insoluble in water

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point:

Heat of combustion:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

-42 °C (Propellant)

Non-applicable *

Non-applicable *

0,8 % Volume

18,6 % Volume

Explosive:

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) **Page 8/14**



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 10: STABILITY AND REACTIVITY (continued)

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable Not applicable		Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids Water		Oxidising materials	Combustible materials	Others	
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Ethylbenzene (2B); Reaction mass of ethylbenzene and xylene (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	А	cute toxicity	Genus
dimethyl ether	LD50 oral	>2000 mg/kg	
CAS: 115-10-6	LD50 dermal	>2000 mg/kg	
EC: 204-065-8	LC50 inhalation	308,5 mg/L (4 h)	Rat
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50 oral	5840 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	2920 mg/kg	Rat
EC: 921-024-6	LC50 inhalation	>20 mg/L (4 h)	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 926-605-8	LC50 inhalation	>20 mg/L (4 h)	
Reaction mass of ethylbenzene and xylene	LD50 oral	2100 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	1100 mg/kg	Rat
EC: 905-588-0	LC50 inhalation	11 mg/L (4 h)	Rat
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Chlorobenzene	LD50 oral	>2000 mg/kg	
CAS: 108-90-7	LD50 dermal	>2000 mg/kg	
EC: 203-628-5	LC50 inhalation	11 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LC50	5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: Non-applicable	EC50	Non-applicable			
EC: 921-024-6	EC50	Non-applicable			
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	LC50	>1 - 10 mg/L (96 h)		Fish	
CAS: Non-applicable	EC50	>1 - 10 mg/L (48 h)		Crustacean	
EC: 926-605-8	EC50	>1 - 10 mg/L (72 h)		Algae	
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae	
Chlorobenzene	LC50	7.4 mg/L (96 h)	Lepomis macrochirus	Fish	
CAS: 108-90-7	EC50	19.9 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 203-628-5	EC50	12.5 mg/L (96 h)	Selenastrum capricornutum	Algae	

12.2 Persistence and degradability:

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 10/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	BOD5	Non-applicable	Concentration	Non-applicable
CAS: Non-applicable	COD	Non-applicable	Period	28 days
EC: 921-024-6	BOD5/COD	Non-applicable	% Biodegradable	98 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Chlorobenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-90-7	COD	Non-applicable	Period	28 days
EC: 203-628-5	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Reaction mass of ethylbenzene and xylene	BCF	9	
CAS: Non-applicable	Pow Log	2.77	
EC: 905-588-0	Potential	Low	
Ethylbenzene	BCF	1	
CAS: 100-41-4	Pow Log	3.15	
EC: 202-849-4	Potential	Low	
Chlorobenzene	BCF	22	
CAS: 108-90-7	Pow Log	2.84	
EC: 203-628-5	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
dimethyl ether	Koc	Non-applicable	Henry	Non-applicable
CAS: 115-10-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-065-8	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene	Koc	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
Chlorobenzene	Koc	Non-applicable	Henry	Non-applicable
CAS: 108-90-7	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-628-5	Surface tension	3,293E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code Description		Waste class (Regulation (EU) No 1357/2014)	
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 11/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es): 2

 Labels: 2.1

 14.4 Packing group: N/A
 14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 190, 327, 344, 625

Tunnel restriction code: D

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

 14.3
 Transport hazard class(es):
 2

 Labels:
 2.1

 14.4
 Packing group:
 N/A

 14.5
 Marine pollutant:
 Yes

14.6 Special precautions for user

Special regulations: 63, 959, 190, 277, 327, 344

EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: Non-applicable

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

Labels: 2.1 **14.4 Packing group:** N/A **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

14.3 Transport hazard class(es):

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according** Non-applicable

to Annex II of Marpol and

the IBC Code:

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 12/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Substances that contribute to the classification (SECTION 2):

· New declared substances

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Reaction mass of ethylbenzene and xylene

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

Date of compilation: 04/06/2014 Revised: 21/05/2021 Version: 5 (Replaced 4) Page 13/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

GRUNT DO TWORZYW SZTUCZNYCH SPRAY - PLASTIC PRIMER - SPRAY

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Gas 1A: H220 - Extremely flammable gas. Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Aerosol 1: Calculation method Skin Irrit. 2: Calculation method Eye Irrit. 2: Calculation method STOT SE 3: Calculation method Aquatic Chronic 2: Calculation method STOT RE 2: Calculation method Aerosol 1: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -