



PLASTIC PRIMER SPRAY



EAN code: 5907588403245 item no.: 0010122 colourless

+ PROPERTIES

Primer for plastics is a one-component, fast drying primer spray that enhances adhesion between the plastic surface and the topcoat. Due to its flexibility it is used as a primer before painting plastic car parts such as bumpers, spoilers, etc.

• COLOUR

colourless

☞ METHOD OF USE

Thoroughly clean and degrease and then dry the areas to be covered with paint. Before applying the primer, it is recommended to matt the surface and to clean and degrease it again. Cover adhering surfaces with paper. Shake the container well for about 3 minutes before use. When painting, keep the container at a distance of 15-20 cm from the surface to be coated. After about 45 minutes the surface can be varnished. After use, invert the container and spray until the valve is empty.

↓ APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface



Shake thoroughly



Spray 1-2 layers from a distance of about 15-20 cm



Flash-off time between layer: 5 ÷ 10 minutes



After about 45 minutes the surface can be varnished



Spray until the valve is empty



PHYSICAL PROPERTIES

boiling point:	-24°C
autoignition temperature:	215°C
flash point:	-42°C
solvents:	aliphatic hydrocarbons
density at 20°C:	0,727 g/cm ³
flammability limit:	upper: 18,6 % vol. / lower: 1,1 % vol.
organic solvents:	98,2%



STORAGE CONDITION



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.