



PLASTIC PRIMER SPRAY



EAN code: 5907588403245 item no.: 0010122 clear



PROPERTIES

Plastic primer is a fast drying, one-component spray that increases the adhesion between plastic surfaces and the topcoat. Due to its flexibility it is used before painting plastic car parts such as bumpers, spoilers, etc.



COLOUR

colourless



METHOD OF USE

Thoroughly clean, degrease and then dry the surface. Before applying the primer, we recommend to matt the surface and to clean and degrease it again. Cover adjacent areas with paper. Shake the container well for about 3 minutes before use. When painting, keep the container at 15-20 cm distance of from the surface. After about 45 minutes the surface can be varnished. After use, invert the container and spray until the valve is empty.



APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface



Shake thoroughly



Spray 1-2 layers from a distance of about 15-20 cm



Flash-off time between layer: 5 ÷ 10 minutes



After about 45 minutes the surface can be varnished



Spray until the valve is empty



PHYSICAL PROPERTIES

density at 20°C:

0,727 g/cm³



STORAGE CONDITION



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.