

## ACRYLIC LACQUER FOR WHEELS RALLY SPRAY

EAN code: 5907588490009 item no.: 001013 silver EAN code: 5907588403528 item no.: 0010134 black gloss EAN code: 5907588405225 item no.: 0010135 black mat



### PROPERTIES

Paint for car rims - rally is a paint for internal and external use. It gives car rims and other surfaces a perfect appearance and protects reliably against corrosion and the effects of salt and water. It is also perfect for painting metal, wood, plastic, plaster, brick and paper. Can be used for touch-ups on cars, furniture, for hobby purposes, etc.

| COLOUR |        |                 |
|--------|--------|-----------------|
|        | silver | black gloss/mat |



### METHOD OF USE

Thoroughly clean, degrease and dry the areas to be varnished. Cover adhering surfaces with paper. Shake the container well for about 3 minutes before use. While painting, keep the container at a distance of 15-20 cm from the surface to be painted. After use, invert the container and spray until the valve is empty. Drying time: approx. 90 minutes at 20°C.

# APPLICATION Image: Constraint of the synthesis of the synthesynthesis of the synthesynthesis of the synthesynthesis of the synth




÷

### **PHYSICAL PROPERTIES**

| boiling point:            | -44°C                                  |
|---------------------------|--|
| autoignition temperature: | 365°C                                  |
| flash point:              | < 0°C                                  |
| density at 20°C:          | 0,711 g/cm <sup>3</sup>                |
| flammability limit:       | upper: 13,0 % vol. / lower: 0,7 % vol. |

### **STORAGE CONDITIONS**



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

# SHELF LIFE

24 months from the date of production placed on the package.

### SAFETY

See Safety Data Sheet.

### **OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.