



## ANTICORROSIVE PRIMING PAINT SPRAY

EAN code: 5907588403764 item no.: 001408 red



### PROPERTIES

Anticorrosive primer for surface preparation and long-term protection against corrosion of car body parts. It is primarily used in painting works, but can also be applied in industry or construction. Creates a smooth, protective coating highly resistant to scratching, water, salt, gasoline and most aggressive chemicals. Resistant to corrosion (in accordance with DIN 50021) and high temperatures (for short periods up to +140°C in dry conditions and +80°C in wet conditions).



### COLOUR



oxide red



### METHOD OF USE

Thoroughly clean degrease, and then dry the surface. Cover adjacent areas with paper. Shake the container well for about 3 minutes, before use. When painting, keep the container 15-20 cm from the surface. After use, invert the container and spray until the valve is empty. After approx. 20 minutes (at 20 °C), the surface becomes dust-dry. Total drying time: 24 hours. After this time, the surface can be varnished (a test is recommended). Do not cover with polyester putties.



### SUBSTRATE

- **metal** - sand, blow and degrease with "BOLL silicone remover", and then apply another layer.
- **non-ferrous metals (zinc, aluminum, copper, etc.)** - grind, blow and degrease with "BOLL silicone remover", then apply another layer.
- **old paint coatings** - sand, blow and degrease with "BOLL silicone remover", then apply another layer.
- **polyester putties** - sand, blow and degrease with "BOLL silicone remover", then apply another layer.



## APPLICATION



Thoroughly clean the surface and roughen it



Thoroughly clean and degrease the surface



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Evaporation time between layers: 5 ÷ 10 minutes



After approx. 24 hours, the surface can be covered with most paints and varnishes



After use, invert the container and spray until the valve is empty



## PHYSICAL PROPERTIES

physical state:

aerosol

drying time:

depending on layer thickness, temperature and ventilation



## STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



## SHELF LIFE

24 months from the production date placed on the package.



## SAFETY

See Safety Data Sheet.



## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.