


**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** SZPACHLÓWKA SOFT - SOFT PUTTY  
Mixture identifier: contains: styrene, maleic anhydride, titanium dioxide, reaction product of bisphenol A with epichlorohydrin; epoxy resin (average molecular weight  $\leq 700$ ), 2,2'- (m-tolylimino) diethanol.
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: The product is intended for professional use, used for repairing car bodies and polyester laminates.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna  
ul. Chemiczna 3  
65-713 Zielona Góra - Polska  
Phone.: 68 451 99 99 - Fax: 68 451 99 00  
technolog@boll.pl
- 1.4 Emergency telephone number:**

**SECTION 2: HAZARDS IDENTIFICATION \*\***

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Carc. 2: Carcinogenicity, Category 2, H351  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Repr. 2: Reproductive toxicity, Category 2, H361d  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317  
STOT RE 1: Specific target organ toxicity by inhalation, repeated exposure, Category 1, H372
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H351 - Suspected of causing cancer (Inhalation).  
H361d - Suspected of damaging the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
- Precautionary statements:**  
P260: Do not breathe dust/fume/gas/mist/vapours/spray  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P314: Get medical advice/attention if you feel unwell  
P403+P235: Store in a well-ventilated place. Keep cool  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively
- Supplementary information:**  
EUH212: Warning! Hazardous respirable dust may be formed when used. Do not breathe dust
- Substances that contribute to the classification**  
styrene; Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ )

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SZPACHLÓWKA SOFT - SOFT PUTTY

### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

**Chemical description:** a mixture of organic and auxiliary substances

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-42-5 EC: 202-851-5 Index: 601-026-00-0 REACH: 01-2119457861-32-XXXX	<b>styrene<sup>(1)</sup></b> Self-classified	<15 %
	Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372; STOT SE 3: H335 - Danger	
CAS: 13463-67-7 EC: 236-675-5 Index: Non-applicable REACH: 01-2119489379-17-XXXX	<b>Titanium dioxide (aerodynamic diameter ≤ 10 µm)<sup>(1)</sup></b> Self-classified	<2,5 %
	Regulation 1272/2008 Carc. 2: H351 - Warning	
CAS: 91-99-6 EC: 202-114-8 Index: Non-applicable REACH: Non-applicable	<b>2,2'-(m-tolylimino)diethanol<sup>(1)</sup></b> Self-classified	<0,2 %
	Regulation 1272/2008 Acute Tox. 3: H301; Eye Irrit. 2: H319 - Danger	
CAS: 2687-91-4 EC: 220-250-6 Index: 616-208-00-5 REACH: 01-2119472138-36-XXXX	<b>N-ethyl-2-pyrrolidone<sup>(1)</sup></b> Self-classified	<0,2 %
	Regulation 1272/2008 Eye Dam. 1: H318; Repr. 1B: H360Df - Danger	
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: 01-2119456619-26-XXXX	<b>reaction product: bisphenol-A-(epichlorhydrin) ( MW &lt; 700 )<sup>(1)</sup></b> ATP CLP00	<0,1 %
	Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	
CAS: 108-31-6 EC: 203-571-6 Index: 607-096-00-9 REACH: 01-2119472428-31-XXXX	<b>maleic anhydride<sup>(1)</sup></b> ATP ATP13	<0,05 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT RE 1: H372; EUH071 - Danger	

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification	Specific concentration limit
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319
maleic anhydride CAS: 108-31-6 EC: 203-571-6	% (w/w) >=0,001: Skin Sens. 1A - H317

\*\* Changes with regards to the previous version

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

- CONTINUED ON NEXT PAGE -

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 4: FIRST AID MEASURES (continued)****By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

- CONTINUED ON NEXT PAGE -

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:****A.- Precautions for safe manipulation**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**B.- Technical recommendations for the prevention of fires and explosions**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations to prevent ergonomic and toxicological risks**

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:****A.- Technical measures for storage**

Minimum Temp.:	5 °C
Maximum Temp.:	20 °C
Maximum time:	24 Months

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	306 mg/m <sup>3</sup>	85 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

**SZPACHLÓWKA SOFT - SOFT PUTTY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2,2'-(m-tolylimino)diethanol CAS: 91-99-6 EC: 202-114-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,23 mg/kg	Non-applicable
	Inhalation	0,8 mg/m <sup>3</sup>	Non-applicable	0,8 mg/m <sup>3</sup>	Non-applicable
N-ethyl-2-pyrrolidone CAS: 2687-91-4 EC: 220-250-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	4 mg/kg	Non-applicable
	Inhalation	Non-applicable	20,1 mg/m <sup>3</sup>	16,75 mg/m <sup>3</sup>	10,05 mg/m <sup>3</sup>
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,93 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	174,25 mg/m <sup>3</sup>	182,75 mg/m <sup>3</sup>	10,2 mg/m <sup>3</sup>	Non-applicable
2,2'-(m-tolylimino)diethanol CAS: 91-99-6 EC: 202-114-8	Oral	0,14 mg/kg	Non-applicable	0,14 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,07 mg/kg	Non-applicable
	Inhalation	0,24 mg/m <sup>3</sup>	Non-applicable	0,24 mg/m <sup>3</sup>	Non-applicable
N-ethyl-2-pyrrolidone CAS: 2687-91-4 EC: 220-250-6	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	1,2 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>	1,2 mg/m <sup>3</sup>
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,0893 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,87 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
styrene CAS: 100-42-5 EC: 202-851-5	STP	5 mg/L	Fresh water	0,028 mg/L
	Soil	0,2 mg/kg	Marine water	0,014 mg/L
	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,307 mg/kg
2,2'-(m-tolylimino)diethanol CAS: 91-99-6 EC: 202-114-8	STP	81,7 mg/L	Fresh water	0,107 mg/L
	Soil	0,37 mg/kg	Marine water	0,011 mg/L
	Intermittent	1,07 mg/L	Sediment (Fresh water)	2,16 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,22 mg/kg
N-ethyl-2-pyrrolidone CAS: 2687-91-4 EC: 220-250-6	STP	10 mg/L	Fresh water	0,25 mg/L
	Soil	0,104 mg/kg	Marine water	0,025 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	1,25 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,125 mg/kg
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L
	Soil	0,065 mg/kg	Marine water	0,001 mg/L
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

- CONTINUED ON NEXT PAGE -



**SZPACHLÓWKA SOFT - SOFT PUTTY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Thixotropic
Colour:	■ Grey
Odour:	Aromatic
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	145 °C
Vapour pressure at 20 °C:	665 Pa
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1650 - 1750 kg/m <sup>3</sup>
Relative density at 20 °C:	1,65 - 1,75
Dynamic viscosity at 20 °C:	285000 - 375000 cP
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	2,96
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

**Flammability:**

Flash Point:	32 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	490 °C
Lower flammability limit:	0,9 % Volume
Upper flammability limit:	6,1 % Volume

**Explosive:**

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *
VOC value (VOC) <250 g/l.	
VOC limit value: 250 g/l	

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION \*\*****11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**A- Ingestion (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.  
IARC: styrene (2A); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)****F- Specific target organ toxicity (STOT) - single exposure:**

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
styrene CAS: 100-42-5 EC: 202-851-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	11,8 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$ ) CAS: 13463-67-7 EC: 236-675-5	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L (4 h)	
2,2'-(m-tolylimino)diethanol CAS: 91-99-6 EC: 202-114-8	LD50 oral	100 mg/kg (ATEi)	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
N-ethyl-2-pyrrolidone CAS: 2687-91-4 EC: 220-250-6	LD50 oral	3200 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
maleic anhydride CAS: 108-31-6 EC: 203-571-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	

\*\* Changes with regards to the previous version

**SECTION 12: ECOLOGICAL INFORMATION \*\***

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Species	Genus
styrene CAS: 100-42-5 EC: 202-851-5	LC50	64.7 mg/L (96 h)	Carassius auratus	Fish
	EC50	4.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	67 mg/L (192 h)	Microcystis aeruginosa	Algae
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae

**12.2 Persistence and degradability:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

**SZPACHLÓWKA SOFT - SOFT PUTTY**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
styrene CAS: 100-42-5 EC: 202-851-5	BOD5	1.96 g O2/g	Concentration	100 mg/L
	COD	2.8 g O2/g	Period	14 days
	BOD5/COD	0.7	% Biodegradable	100 %
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
	Parameter	Value
styrene CAS: 100-42-5 EC: 202-851-5	BCF	14
	Pow Log	2.95
	Potential	Low
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) CAS: 25068-38-6 EC: 500-033-5	BCF	4
	Pow Log	2.8
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
styrene CAS: 100-42-5 EC: 202-851-5	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable
maleic anhydride CAS: 108-31-6 EC: 203-571-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,673E-2 N/m (250,21 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

\*\* Changes with regards to the previous version

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

- CONTINUED ON NEXT PAGE -

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 14: TRANSPORT INFORMATION (continued)**

The soft putty has a Classification Certificate No. 125/IPO-BC/2011. It is not subject to RID and ADR regulations on the transport of dangerous goods.

This product is not regulated for transport (ADR/RID,IMDG,IATA)

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION \*\*****Legislation related to safety data sheets:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**SZPACHLÓWKA SOFT - SOFT PUTTY****SECTION 16: OTHER INFORMATION \*\* (continued)**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:****COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):**

## · New declared substances

- Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7)
- 2,2'-(m-tolylimino)diethanol (91-99-6)
- N-ethyl-2-pyrrolidone (2687-91-4)
- reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ) (25068-38-6)
- maleic anhydride (108-31-6)

## · Removed substances

- N-ethyl-2-pyrrolidone (2687-91-4)

**Substances that contribute to the classification (SECTION 2):**

## · New declared substances

- styrene (100-42-5)
- Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7)

**CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):**

- Hazard statements
- Supplementary information

**Texts of the legislative phrases mentioned in section 2:**

- H315: Causes skin irritation
- H361d: Suspected of damaging the unborn child
- H372: Causes damage to organs through prolonged or repeated exposure (Inhalation)
- H351: Suspected of causing cancer (Inhalation)
- H317: May cause an allergic skin reaction
- H226: Flammable liquid and vapour
- H319: Causes serious eye irritation

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

- Acute Tox. 3: H301 - Toxic if swallowed
- Acute Tox. 4: H302 - Harmful if swallowed
- Acute Tox. 4: H332 - Harmful if inhaled
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
- Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
- Carc. 2: H351 - Suspected of causing cancer (Inhalation)
- Eye Dam. 1: H318 - Causes serious eye damage
- Eye Irrit. 2: H319 - Causes serious eye irritation
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Repr. 1B: H360Df - May damage the unborn child. Suspected of damaging fertility
- Repr. 2: H361d - Suspected of damaging the unborn child
- Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage
- Skin Irrit. 2: H315 - Causes skin irritation
- Skin Sens. 1: H317 - May cause an allergic skin reaction
- STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure
- STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation)
- STOT SE 3: H335 - May cause respiratory irritation

**Classification procedure:**

- Skin Irrit. 2: Calculation method
- Repr. 2: Calculation method
- STOT RE 1: Calculation method
- Skin Sens. 1A: Calculation method
- Flam. Liq. 3: Calculation method (2.6.4.3)
- Eye Irrit. 2: Calculation method

**Advice related to training:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

### SZPACHLÓWKA SOFT - SOFT PUTTY

#### SECTION 16: OTHER INFORMATION \*\* (continued)

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -