



## EPOXY PRIMER SPRAY



EAN code: 5907588404563 item no.: 0014014 grey



### PROPERTIES

Epoxy primer spray is a one-component agent for the preservation and protection of various types of metal surfaces. Thanks to the use of special epoxy resins, it is perfect for use directly on sheet metal, aluminum, galvanized steel and old paint coatings. Due to its insulating effect, it has very good adhesion to the surface and high anti-corrosion properties. Quick drying, easy to handle and has good filling properties. It can be covered with most paints and varnishes.



### COLOUR

 grey



### METHOD OF USE

Thoroughly clean and degrease, and then dry the places to be covered with paint. Cover adjoining surfaces with paper. Before use, shake the container well for about 3 minutes. When painting, keep the container 15-20 cm from the surface to be coated. After use, invert the container and spray until the valve is empty.



### SUBSTRATE

- **metal** - sand, blow off and degrease with "BOLL silicone remover", and then apply another layer.

---

- **non-ferrous metals (zinc, aluminum, copper, etc.)** - grind, blow off and degrease with "BOLL silicone remover", and then apply another layer.

---

- **old paint coatings** - sand, blow off, degrease with "BOLL silicone remover", and then apply another layer.

---

- **polyester putties** - sand, blow off and degrease with "BOLL silicone remover", and then apply another layer.



## APPLICATION



Thoroughly clean the surface and roughen it



Thoroughly clean the surface and degrease it



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Flash off time between layers: 5 ÷ 10 minutes



After approx. 12 hours, the surface can be covered with most paints and varnishes



After use, invert the container and spray until the valve is empty



## PHYSICAL PROPERTIES

density:	0,901 g/ml
solids:	about 28%
flammability limit:	upper: 20% vol. / lower: 0,7% vol.
drying time:	depending on layer thickness, temperature and ventilation

### Indications:

dust free:	approx. 40 minutes.
sanding:	after approx. 8 hours
overlapping	
(with the same product):	after approx. 8 hours
overlapping	
(with another product):	after approx. 12 hours



## STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



#### SHELF LIFE

24 months from the date of production placed on the package.



#### SAFETY

See Safety Data Sheet.



#### OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.