



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

Other means of identification:

UFI: 1SDM-F0QT-R00M-61W5

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Polyurethane sealing agent for windscreen.. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa BOLL Wojciech Dalewski Spółka Jawna
ul. Chemiczna 3
65-713 Zielona Góra - Polska
Phone: 68 451 99 99 - Fax: 68 451 99 00
huszcza@boll.pl

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334

Skin Irrit. 2: Skin irritation, Category 2, H315

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261: Avoid breathing vapours.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Substances that contribute to the classification

4,4'-methylenediphenyl diisocyanate

Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

UFI: 1SDM-F0QT-R00M-61W5

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: a mixture containing a polyurethane prepolymer based on methylene diphenyl diisocyanate.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1333-86-4 EC: 215-609-9 Index: Non-applicable REACH: Non-applicable	Carbon black⁽¹⁾ Not classified Regulation 1272/2008	10 - <30 %
CAS: Non-applicable EC: 926-141-6 Index: Non-applicable REACH: 01-2119456620-43-XXXX	Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾ Self-classified Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger	1 - <5 %
CAS: 101-68-8 EC: 202-966-0 Index: 615-005-00-9 REACH: 01-2119457014-47-XXXX	4,4'-methylenediphenyl diisocyanate⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	<1 %
CAS: 683-18-1 EC: 211-670-0 Index: 050-022-00-X REACH: 01-2119496066-31-XXXX	Dibutyltin dichloride⁽¹⁾ ATP ATP01 Regulation 1272/2008 Acute Tox. 2: H330; Acute Tox. 3: H301; Acute Tox. 4: H312; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Muta. 2: H341; Repr. 1B: H360FD; Skin Corr. 1B: H314; STOT RE 1: H372 - Danger	<0,1 %
CAS: 1461-22-9 EC: 215-958-7 Index: 050-008-00-3 REACH: 01-2119471989-14-XXXX	Tributyltin chloride⁽¹⁾ ATP ATP07 Regulation 1272/2008 Acute Tox. 3: H301; Acute Tox. 4: H332; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Repr. 1B: H360FD; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	<0,001 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
	Acute	Chronic
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	10	10
Tributyltin chloride CAS: 1461-22-9 EC: 215-958-7	10	10

Identification	Specific concentration limit
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	% (w/w) >=5: Skin Corr. 1B - H314 0,01<= % (w/w) <5: Skin Irrit. 2 - H315 % (w/w) >=3: Eye Dam. 1 - H318 0,01<= % (w/w) <3: Eye Irrit. 2 - H319
Tributyltin chloride CAS: 1461-22-9 EC: 215-958-7	% (w/w) >=1: Skin Irrit. 2 - H315 % (w/w) >=1: Eye Irrit. 2 - H319 % (w/w) >=1: STOT RE 1 - H372 0,25<= % (w/w) <1: STOT RE 2 - H373

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Nuisance dust: Inhalable dust 10 mg/m³ // Respirable dust 4 mg/m³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,1 mg/m ³	Non-applicable	0,05 mg/m ³
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	1 mg/kg	Non-applicable	0,2 mg/kg	Non-applicable
	Inhalation	0,07 mg/m ³	Non-applicable	0,01 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,05 mg/m ³	Non-applicable	0,025 mg/m ³
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	Oral	0,01 mg/kg	Non-applicable	0,002 mg/kg	Non-applicable
	Dermal	0,5 mg/kg	Non-applicable	0,08 mg/kg	Non-applicable
	Inhalation	0,02 mg/m ³	Non-applicable	0,003 mg/m ³	Non-applicable

PNEC:



Identification				
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	STP	0,115 mg/L	Fresh water	0,001 mg/L
	Soil	0,002 mg/kg	Marine water	0 mg/L
	Intermittent	0,008 mg/L	Sediment (Fresh water)	0,007 mg/kg
	Oral	0,0002 g/kg	Sediment (Marine water)	0,001 mg/kg

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Solid
 Appearance: Paste
 Colour: Black
 Odour: Odourless
 Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: ≥190 °C
 Vapour pressure at 20 °C: Non-applicable *
 Vapour pressure at 50 °C: Non-applicable *
 Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1230 kg/m³
 Relative density at 20 °C: 1,23
 Dynamic viscosity at 20 °C: Non-applicable *
 Kinematic viscosity at 20 °C: Non-applicable *
 Kinematic viscosity at 40 °C: >20,5 mm²/s
 Concentration: Non-applicable *
 pH: Non-applicable *
 Vapour density at 20 °C: Non-applicable *
 Partition coefficient n-octanol/water 20 °C: Non-applicable *
 Solubility in water at 20 °C: Non-applicable *
 Solubility properties: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature:	≥140 °C
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	>90 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	≥200 °C
Lower flammability limit:	0,6 % Volume
Upper flammability limit:	7 % Volume
Explosive (Solid):	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
Particle characteristics:	
Median equivalent diameter:	Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT****SECTION 11: TOXICOLOGICAL INFORMATION ******11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Carbon black (2B); 4,4'-methylenediphenyl diisocyanate (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Carbon black	LD50 oral	>2000 mg/kg	
CAS: 1333-86-4	LD50 dermal	>2000 mg/kg	
EC: 215-609-9	LC50 inhalation	>5 mg/L	

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 926-141-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LD50 oral	7616 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	LD50 oral	219 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Tributyltin chloride CAS: 1461-22-9 EC: 215-958-7	LD50 oral	129 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

11.2 Information on other hazards:**Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50	EC50		
Carbon black CAS: 1333-86-4 EC: 215-609-9	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	5600 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	LC50	4 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	0,05 mg/L (48 h)	N/A	Crustacean
	EC50	8 mg/L (72 h)	Scenedesmus subspicatus	Algae
Tributyltin chloride CAS: 1461-22-9 EC: 215-958-7	LC50	0,01 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	0,018 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,0124 mg/L (96 h)	Selenastrum capricornutum	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	NOEC		
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	NOEC	Non-applicable		
	NOEC	10 mg/L	Daphnia magna	Crustacean
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	NOEC	0,04 mg/L	Oncorhynchus mykiss	Fish
	NOEC	0,002 mg/L	Mytilus edulis	Crustacean

12.2 Persistence and degradability:**Substance-specific information:**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	20 mg/L
Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	6 %

12.3 Bioaccumulative potential:**Substance-specific information:**

Identification	Bioaccumulation potential	
	BCF	Pow Log
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	150	4.51
	Potential	High
	Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	135
Pow Log		0.97
Potential		High
Tributyltin chloride CAS: 1461-22-9 EC: 215-958-7	1976	2.21
	Pow Log	2.21
	Potential	Very High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	Non-applicable
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,068E-2 N/m (283,45 °C)	Moist soil	Non-applicable
	Dibutyltin dichloride CAS: 683-18-1 EC: 211-670-0	Koc	23	Henry
Conclusion		Very High	Dry soil	Non-applicable
Surface tension		Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Dibutyltin dichloride

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Dibutyltin dichloride ; Tributyltin chloride

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 15: REGULATORY INFORMATION (continued)

Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of Regulation (EU) 2016/425.

Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste

— any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 15: REGULATORY INFORMATION (continued)

(b) intermediate level training, including on-line training, on:

- additional behaviour-based aspects
- maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
- certification or documented proof that training has been successfully completed

(c) advanced training, including on-line training, on:

- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture (s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law

(b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates

(c) national exposure limits for diisocyanates, if there are any

(d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
 - Carbon black (1333-86-4)
 - Tributyltin chloride (1461-22-9)
 - Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements
- Supplementary information

Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

KLEJ DO SZYB SAMOCHODOWYCH SPRINT - ADHESIVE FOR WINDSCREEN SPRINT

SECTION 16: OTHER INFORMATION (continued)

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H412: Harmful to aquatic life with long lasting effects.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 4: H312 - Harmful in contact with skin.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Muta. 2: H341 - Suspected of causing genetic defects.

Repr. 1B: H360FD - May damage fertility. May damage the unborn child.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Resp. Sens. 1: Calculation method

Aquatic Chronic 3: Calculation method

Skin Irrit. 2: Calculation method

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -