

ACRYLIC LACQUER FOR WHEELS- RALLY

EAN code: 5907588404860 item no.: 001425 silver, cap.500ml EAN code: 5907588404884 item no.: 001427 black gloss, cap.500ml EAN code: 5907588405232 item no.: 001429 black matt, cap.500ml EAN code: 5907588404877 item no.: 001426 silver, cap.1000ml EAN code: 5907588404891 item no.: 001428 black gloss, cap.1000ml EAN code: 5907588405249 item no.: 001430 black matt, cap.1000ml

PROPERTIES

Fast-drying paint for the indoor and outdoor use, with a very high adhesion to the substrate. Gives car rims an attractive appearance and protects them against adverse weather conditions. It can also be used for painting plastics, wood, plaster and various metals. Available in silver and black.

| silver black gloss/mat | |
|------------------------|--|



METHOD OF USE

Thoroughly clean, degrease and then dry the surface. Cover adjacent areas with masking materials. Before use, thoroughly mix the contents of the can. The varnish can be applied with a spray gun or appropriate brush or roller. For the best effect, we recommend to apply two layers. The second layer can be applied after the first is dust dry.

| | ION | | |
|-------|---|--------------|--|
| | Thoroughly clean and degrease the surface | | |
| | Viscosity: | | |
| | DIN 4 20°C | | |
| | 19 - 21 s | | |
| | Nozzle | 1,3 - 1,6 mm | |
| | Pressure | 2 – 2,5 bar | |
| | Layers | 2 | |
|)tsts | Drying time 5 - 10 min | | |
| | | | |
| | | | |

STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.

XI SHELF LIFE

24 months from the production date placed on the package.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.