




NEUTRALIZATOR RDZY SPRAY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** NEUTRALIZATOR RDZY SPRAY
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Rust neutralizer.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna
ul. Chemiczna 3
65-713 Zielona Góra - Polska
Phone.: 68 451 99 99 - Fax: 68 451 99 00
technolog@boll.pl
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT RE 2: Specific target organ toxicity if swallowed, repeated exposure, Category 2, H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
- 
- Hazard statements:**
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- Precautionary statements:**

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 2: HAZARDS IDENTIFICATION (continued)

P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source
P251: Do not pierce or burn, even after use
P260: Do not breathe dust/fume/gas/mist/vapours/spray
P264: Wash the hands thoroughly after handling
P280: Wear protective gloves/protective clothing/eye protection/face protection
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310: Immediately call a poison center/doctor
P321: Specific treatment is urgently needed (go to see a doctor with the Safety data sheet for this product)
P333+P313: If skin irritation or rash occurs: Get medical advice/attention
P403+P233: Store in a well-ventilated place. Keep container tightly closed
P405: Store locked up
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

EUH208: Contains Epichlorohydrin/Bisphenol-A epoxy resin (700 < MW < 1100). May produce an allergic reaction

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: active ingredient mixture with a propellant. Extruding gas: dimethyl ether

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	Dimethyl ether⁽¹⁾ ATP CLP00		25 - <50 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	Acetone⁽¹⁾ ATP CLP00		10 - <25 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene⁽¹⁾ Self-classified		10 - <25 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	Propan-2-ol⁽¹⁾ ATP CLP00		2,5 - <10 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	1-methoxy-2-propanol⁽¹⁾ ATP ATP01		2,5 - <10 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 71-36-3 EC: 200-751-6 Index: 603-004-00-6 REACH: 01-2119484630-38-XXXX	1-butanol⁽¹⁾ ATP CLP00		2,5 - <10 %
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification		Concentration
CAS: 25036-25-3 EC: Non-applicable Index: Non-applicable REACH: Non-applicable	Epichlorohydrin/Bisphenol-A epoxy resin (700 < MW < 1100)⁽¹⁾ Self-classified		1 - <2,5 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	Isobutanol⁽¹⁾ ATP CLP00		0,1 - <1 %
	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification		Environmental limits	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (8h)	1000 ppm	1920 mg/m ³
	IOELV (STEL)		
Acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m ³
	IOELV (STEL)		
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	IOELV (8h)	100 ppm	375 mg/m ³
	IOELV (STEL)	150 ppm	563 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1879 - 1909 mg/m ³	Non-applicable
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	171 - 201 mg/kg	Non-applicable
	Inhalation	Non-applicable	2405 - 2435 mg/m ³	1195 - 1225 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	165 - 195 mg/kg	Non-applicable
	Inhalation	274 - 304 mg/m ³	274 - 304 mg/m ³	62 - 92 mg/m ³	Non-applicable
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	873 - 903 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	485 - 515 mg/m ³	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	35,6 - 65,6 mg/kg	Non-applicable
	Inhalation	Non-applicable	538,5 - 568,5 mg/m ³	354 - 384 mg/m ³	Non-applicable
1-butanol CAS: 71-36-3 EC: 200-751-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	295 - 325 mg/m ³
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	295 - 325 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	456 - 486 mg/m ³	Non-applicable
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	47 - 77 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	47 - 77 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	185 - 215 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	-13,4 - 16,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	93 - 123 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-0,2 - 29,8 mg/m ³	Non-applicable
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	11 - 41 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	304 - 334 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	74 - 104 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	-11,7 - 18,3 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	3,1 - 33,1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	28,9 - 58,9 mg/m ³	Non-applicable
1-butanol CAS: 71-36-3 EC: 200-751-6	Oral	Non-applicable	Non-applicable	-11,88 - 18,13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	40 - 70 mg/m ³
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	10 - 40 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	40 - 70 mg/m ³

PNEC:

Identification					
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	145 - 175 mg/L	Fresh water	-14,85 - 15,16 mg/L	
	Soil	-14,96 - 15,05 mg/kg	Marine water	-14,98 - 15,02 mg/L	
	Intermittent	-13,45 - 16,55 mg/L	Sediment (Fresh water)	-14,32 - 15,68 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,93 - 15,07 mg/kg	
Acetone CAS: 67-64-1 EC: 200-662-2	STP	85 - 115 mg/L	Fresh water	-4,4 - 25,6 mg/L	
	Soil	14,5 - 44,5 mg/kg	Marine water	-13,94 - 16,06 mg/L	
	Intermittent	6 - 36 mg/L	Sediment (Fresh water)	15,4 - 45,4 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-11,96 - 18,04 mg/kg	
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	-8,42 - 21,58 mg/L	Fresh water	-14,67 - 15,33 mg/L	
	Soil	-12,69 - 17,31 mg/kg	Marine water	-14,67 - 15,33 mg/L	
	Intermittent	-14,67 - 15,33 mg/L	Sediment (Fresh water)	-2,54 - 27,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-2,54 - 27,46 mg/kg	
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2236 - 2266 mg/L	Fresh water	125,9 - 155,9 mg/L	
	Soil	13 - 43 mg/kg	Marine water	125,9 - 155,9 mg/L	
	Intermittent	125,9 - 155,9 mg/L	Sediment (Fresh water)	537 - 567 mg/kg	
	Oral	145 - 175 g/kg	Sediment (Marine water)	537 - 567 mg/kg	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	STP	85 - 115 mg/L	Fresh water	-5 - 25 mg/L	
	Soil	-9,51 - 20,49 mg/kg	Marine water	-14 - 16 mg/L	
	Intermittent	85 - 115 mg/L	Sediment (Fresh water)	37,3 - 67,3 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-9,8 - 20,2 mg/kg	
1-butanol CAS: 71-36-3 EC: 200-751-6	STP	2461 - 2491 mg/L	Fresh water	-14,92 - 15,08 mg/L	
	Soil	-14,99 - 15,02 mg/kg	Marine water	-14,99 - 15,01 mg/L	
	Intermittent	-12,75 - 17,25 mg/L	Sediment (Fresh water)	-14,82 - 15,18 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,98 - 15,02 mg/kg	
Isobutanol CAS: 78-83-1 EC: 201-148-0	STP	-5 - 25 mg/L	Fresh water	-14,6 - 15,4 mg/L	
	Soil	-14,93 - 15,07 mg/kg	Marine water	-14,96 - 15,04 mg/L	
	Intermittent	-4 - 26 mg/L	Sediment (Fresh water)	-13,48 - 16,52 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,85 - 15,15 mg/kg	

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



- CONTINUED ON NEXT PAGE -





NEUTRALIZATOR RDZY SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	 CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	98 % weight
V.O.C. density at 20 °C:	676 kg/m ³ (676 g/L)
Average carbon number:	4,7
Average molecular weight:	78,45 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	 Amber
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	-25 °C
Vapour pressure at 20 °C:	520000 Pa
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	800 kg/m ³
Relative density at 20 °C:	0,8
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20,5 cSt
Concentration:	Non-applicable *
pH:	2,5
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	-41 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	1,1 % Volume
Upper flammability limit:	20 % Volume

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Xylene (3); Propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	308,5 mg/L (4 h)	Rat
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72,6 mg/L (4 h)	Rat
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
1-butanol CAS: 71-36-3 EC: 200-751-6	LD50 oral	2292 mg/kg	Rat
	LD50 dermal	3400 mg/kg	Rabbit
	LC50 inhalation	24,66 mg/L (4 h)	Rat
Epichlorohydrin/Bisphenol-A epoxy resin (700 < MW < 1100) CAS: 25036-25-3 EC: Non-applicable	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Isobutanol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24,6 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Species	Genus
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
1-butanol CAS: 71-36-3 EC: 200-751-6	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae
Isobutanol CAS: 78-83-1 EC: 201-148-0	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	BOD5	1.19 g O ₂ /g	Concentration	100 mg/L
	COD	2.23 g O ₂ /g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
1-butanol CAS: 71-36-3 EC: 200-751-6	BOD5	1.71 g O ₂ /g	Concentration	Non-applicable
	COD	2.46 g O ₂ /g	Period	19 days
	BOD5/COD	0.69	% Biodegradable	98 %
Isobutanol CAS: 78-83-1 EC: 201-148-0	BOD5	0.4 g O ₂ /g	Concentration	100 mg/L
	COD	2.41 g O ₂ /g	Period	14 days
	BOD5/COD	0.17	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	BCF	3
	Pow Log	0.05
	Potential	Low
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BCF	3
	Pow Log	-0.44
	Potential	Low
1-butanol CAS: 71-36-3 EC: 200-751-6	BCF	1
	Pow Log	0.88
	Potential	Low

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Isobutanol	BCF	3
CAS: 78-83-1	Pow Log	0.76
EC: 201-148-0	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable
Acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Propan-2-ol CAS: 67-63-0 EC: 200-661-7	Koc	1.5	Henry	8,207E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
1-butanol CAS: 71-36-3 EC: 200-751-6	Koc	2.44	Henry	5,39E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,567E-2 N/m (25 °C)	Moist soil	Yes
Isobutanol CAS: 78-83-1 EC: 201-148-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to ADR 2017 and RID 2017:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 190, 327, 344, 625 |
| Tunnel restriction code: | D |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- | | |
|---|-----------------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 190, 277, 327, 344, 63, 959 |
| EmS Codes: | F-D, S-U |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| Segregation group: | Non-applicable |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2018:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Acetone. Product under the provisions of Article 9

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol

H315: Causes skin irritation

H318: Causes serious eye damage

H317: May cause an allergic skin reaction

H336: May cause drowsiness or dizziness

H373: May cause damage to organs through prolonged or repeated exposure (Oral)

H229: Pressurised container: May burst if heated

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Dam. 1: H318 - Causes serious eye damage

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Gas 1: H220 - Extremely flammable gas

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Press. Gas: H280 - Contains gas under pressure, may explode if heated

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

- CONTINUED ON NEXT PAGE -



NEUTRALIZATOR RDZY SPRAY

SECTION 16: OTHER INFORMATION (continued)

Aerosol 1: Calculation method
Skin Irrit. 2: Calculation method
Eye Dam. 1: Calculation method
Skin Sens. 1: Calculation method
STOT SE 3: Calculation method
STOT RE 2: Calculation method
Aerosol 1: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol–water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -