



RUST CONVERTOR SPRAY

EAN code: 5907588406079 item no.: 00140191 cap. 150ml

EAN code: 5907588406086 item no.: 00140192 cap. 400ml



PROPERTIES

It is a product based on high quality epoxy resins. Thanks to its formulation it has excellent priming and anticorrosive properties. It serves as a primer and a base for subsequent coats, which can be various types of paints, varnishes and polyester putties. It has a wide variety of applications and can be applied directly to rust. Actively works on rust, creating organic iron compounds that block corrosion and a protective epoxy coating.



COLOUR



amber



METHOD OF USE

Remove loose fragments of rust, clean, degrease and then dry the surface. Before use, shake the container for approx. 3 minutes. Apply in 2-3 layers from 20-30 cm distance. Can be painted with most paints and topcoats after 6 hours at a temp. 20°C. We recommend to test the suitability of the product in a given application.



APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface



Mix thoroughly



Apply 2 to 3 coats from a distance of 15-20 cm



Evaporation time between layers: 5 ÷ 10 minutes



Can be painted with most paints and topcoats after 6 hours at a temp. 20°C



After use, invert the container and spray until the valve is empty



PHYSICAL PROPERTIES

physical state:	aerosol
density (at 20°C):	0,794 g/cm ³
drying time:	6h at 20°C
application temperature:	10 ÷ 25°C



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

Two years from the production date on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.