

TECHNICAL DATA SHEET RUST CONVERTOR SPRAY

EAN code: 5907588406079 item no.: 00140191 cap. 150 ml **EAN code:** 5907588406086 item no.: 00140192 cap. 400 ml



+|

PROPERTIES

It is a product based on high-quality epoxy resins. Thanks to its formulation, it has excellent priming and anticorrosive properties. At the same time, it acts as a primer and also as a primer for subsequent layers, which can be various types of paints, varnishes and polyester putties. It has a wide variety of applications and can be applied directly to rust. It actively acts on rust with the formation of blocking organic iron compounds and a protective epoxy coating against corrosion.



COLOUR



amber



METHOD OF USE

Remove loose rust fragments, clean, degrease and then dry the surface to be covered. Can be painted with most paints and topcoats after 6 hours at 20°C. A test is recommended to verify the compatibility of the product in your application.



APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm





Can be painted with most paints and varnishes after 6 hours at 20°C



After use, turn the container over and spray until the valve is empty

#

PHYSICAL PROPERTIES

Physical state: aerosol

Temperature of application: $+15^{\circ}\text{C} - +25^{\circ}\text{C}$

6

STORAGE







Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

四

SHELF LIFE

Two years from the production date placed on the package.

!

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.