

NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier: NEUTRALIZATOR RDZY - RUST CONVERTOR 1.1

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: For use in rust and corrosion protection systems.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna ul. Chemiczna 3 65-713 Zielona Góra - Polska Phone.: 68 451 99 99 - Fax: 68 451 99 00 technolog@boll.pl

Emergency telephone number: 1.4

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Dange



Hazard statements:

- H225 Highly flammable liquid and vapour
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled

H335 - May cause respiratory irritation

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe spray

P270: Do not eat, drink or smoke when using this product

P280: Wear protective gloves/eye protection

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312: Call a POISON CENTER/doctor if you feel unwell

P333+P313: If skin irritation or rash occurs: Get medical advice/attention

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

Additional labeling:

Contains: 4-methylpentan-2-one, formic acid

2.3 **Other hazards:**

Product fails to meet PBT/vPvB criteria



Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU (THIS SDS IS JUST FOR INFORMATIVE PURPOSE. THE SDS SHALL BE SUPPLIED IN AN OFFICIAL LANGUAGE OF THE COUNTRY WHERE THE PRODUCT IS PLACED ON THE MARKET)

NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of organic substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
	108-10-1	4-methylpentan-2-o	ne ⁽¹⁾ ATP CLP00	
REACH:	203-550-1 606-004-00-4 01-2119473980-30- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH066 - Danger	30 - <50 %
	1330-20-7	Xylene ⁽¹⁾	ATP CLP00	
Index: REACH:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	10 - <20 %
	108-65-6 203-603-9	2-methoxy-1-methy	lethyl acetate ⁽¹⁾ ATP ATP01	
Index: 60 REACH: 01	607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	5 - <10 %
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35- XXXX	1-methoxy-2-propanol ⁽¹⁾ ATP ATP01		
Index: REACH:		Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	3 - <6 %
	64-18-6	Formic acid ⁽¹⁾	ATP CLP00	
EC: 200-579-1 Index: 607-001-00-0 REACH: 01-2119491174 XXXX	607-001-00-0 01-2119491174-37-	Regulation 1272/2008	Skin Corr. 1A: H314 - Danger	<2,5 %
	78-83-1	2-methylpropan-1-o	(1) ATP CLP00	
Index: REACH:	201-148-0 603-108-00-1 01-2119484609-23- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	1 - <2 %
	71-36-3	butan-1-ol ⁽¹⁾	Self-classified	
Index: REACH:	200-751-6 603-004-00-6 01-2119484630-38- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	1 - <2 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
CAS: 64-18-6 EC: 200-579-1	% (w/w) >=90: Skin Corr. 1A - H314 10<= % (w/w) <90: Skin Corr. 1B - H314 2<= % (w/w) <10: Skin Irrit. 2 - H315 % (w/w) >=10: Eye Dam. 1 - H318 2<= % (w/w) <10: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.



Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU (THIS SDS IS JUST FOR INFORMATIVE PURPOSE. THE

SDS SHALL BE SUPPLIED IN AN OFFICIAL LANGUAGE OF THE COUNTRY WHERE THE PRODUCT IS PLACED ON THE MARKET)

NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 4: FIRST AID MEASURES (continued)

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO_2). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:



NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:20 °CMaximum time:24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occu	Occupational exposure limits		
4-methylpentan-2-one	IOELV (8h)	20 ppm	83 mg/m ³	
CAS: 108-10-1 EC: 203-550-1	IOELV (STEL)	50 ppm	208 mg/m ³	
Xylene	IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m ³	
CAS: 107-98-2 EC: 203-539-1	IOELV (STEL)	150 ppm	563 mg/m ³	
Formic acid	IOELV (8h)	5 ppm	9 mg/m ³	
CAS: 64-18-6 EC: 200-579-1	IOELV (STEL)			

DNEL (Workers):



NEUTRALIZATOR RDZY - RUST CONVERTOR

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	11,8 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	208 mg/m ³	208 mg/m ³	83 mg/m ³	83 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Non-applicable
Formic acid	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64-18-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 200-579-1	Inhalation	Non-applicable	Non-applicable	Non-applicable	9,5 mg/m ³
2-methylpropan-1-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³

DNEL (General population):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	155,2 mg/m ³	155,2 mg/m ³	14,7 mg/m ³	14,7 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m ³	Non-applicable
Formic acid	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64-18-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 200-579-1	Inhalation	Non-applicable	Non-applicable	Non-applicable	3 mg/m ³
2-methylpropan-1-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m ³

PNEC:

Identification				
4-methylpentan-2-one	STP	27,5 mg/L	Fresh water	0,6 mg/L
CAS: 108-10-1	Soil	1,3 mg/kg	Marine water	0,06 mg/L
EC: 203-550-1	Intermittent	1,5 mg/L	Sediment (Fresh water)	8,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,83 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	10 mg/L
CAS: 107-98-2	Soil	4,59 mg/kg	Marine water	1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg



NEUTRALIZATOR RDZY - RUST CONVERTOR

Identification				
Formic acid	STP	7,2 mg/L	Fresh water	2 mg/L
CAS: 64-18-6	Soil	1,5 mg/kg	Marine water	0,2 mg/L
EC: 200-579-1	Intermittent	1 mg/L	Sediment (Fresh water)	13,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	1,34 mg/kg
2-methylpropan-1-ol	STP	10 mg/L	Fresh water	0,4 mg/L
CAS: 78-83-1	Soil	0,076 mg/kg	Marine water	0,04 mg/L
EC: 201-148-0	Intermittent	11 mg/L	Sediment (Fresh water)	1,56 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,156 mg/kg

8.2 **Exposure controls:**

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.



NEUTRALIZATOR RDZY - RUST CONVERTOR

F.- Additional emergency measures Emergency measure Standards Emergency measure Standards **()**+ ANSI Z358-1 DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 ISO 3864-1:2011, ISO 3864-4:2011 Emergency shower Eyewash stations **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical p	properties:
	For complete information see the product datashee	et.
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Fluid
	Colour:	Amber
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	Non-applicable *
	Vapour pressure at 20 °C:	1540 Pa
	Vapour pressure at 50 °C:	7384,71 Pa (7,38 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	930 kg/m³
	Relative density at 20 °C:	0,93
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Insoluble
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	14 °C
	Flammability (solid, gas):	Non-applicable *
	*Not relevant due to the nature of the product, not providing	information property of its hazards.



Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU (THIS SDS IS JUST FOR INFORMATIVE PURPOSE. THE SDS SHALL BE SUPPLIED IN AN OFFICIAL LANGUAGE OF THE COUNTRY WHERE THE PRODUCT IS PLACED ON THE MARKET)

NEUTRALIZATOR RDZY - RUST CONVERTOR

SEC	TON 9: PHYSICAL AND CHEMICAL PROPERTIES	5 (continued)
	Autoignition temperature:	287 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing infor	mation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):



NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: 4-methylpentan-2-one (2B); Xylene (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	cute toxicity	Genus
4-methylpentan-2-one	LD50 oral	2080 mg/kg	
CAS: 108-10-1	LD50 dermal	>2000 mg/kg	
EC: 203-550-1	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
1-methoxy-2-propanol	LD50 oral	>2000 mg/kg	
CAS: 107-98-2	LD50 dermal	>2000 mg/kg	
EC: 203-539-1	LC50 inhalation	>20 mg/L (4 h)	
Formic acid	LD50 oral	>2000 mg/kg	
CAS: 64-18-6	LD50 dermal	>2000 mg/kg	
EC: 200-579-1	LC50 inhalation	>20 mg/L (4 h)	



NEUTRALIZATOR RDZY - RUST CONVERTOR

Identification	А	Acute toxicity		
2-methylpropan-1-ol	LD50 oral	3350 mg/kg	Rat	
CAS: 78-83-1	LD50 dermal	2460 mg/kg	Rabbit	
EC: 201-148-0	LC50 inhalation	24,6 mg/L (4 h)	Rat	
butan-1-ol	LD50 oral	2292 mg/kg	Rat	
CAS: 71-36-3	LD50 dermal	3400 mg/kg	Rabbit	
EC: 200-751-6	LC50 inhalation	24,66 mg/L (4 h)	Rat	

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
4-methylpentan-2-one	LC50	900 mg/L (48 h)	Leuciscus idus	Fish
CAS: 108-10-1	EC50	862 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-550-1	EC50	980 mg/L (48 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
Formic acid	LC50	175 mg/L (24 h)	Lepomis macrochirus	Fish
CAS: 64-18-6	EC50	120 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-579-1	EC50	26.9 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methylpropan-1-ol	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
CAS: 78-83-1	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-148-0	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
butan-1-ol	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
CAS: 71-36-3	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-751-6	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	Degr	adability	Biodegradal	bility
4-methylpentan-2-one	BOD5	2.06 g O2/g	Concentration	100 mg/L
CAS: 108-10-1	COD	2.16 g O2/g	Period	14 days
EC: 203-550-1	BOD5/COD	0.95	% Biodegradable	84 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
Formic acid	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64-18-6	COD	Non-applicable	Period	14 days
EC: 200-579-1	BOD5/COD	Non-applicable	% Biodegradable	110 %



NEUTRALIZATOR RDZY - RUST CONVERTOR

Identification	Deg	gradability		Bior	degradab	pility	
2-methylpropan-1-ol	BOD5	0.4 g O2/g	Conce	entration		100 mg/L	
CAS: 78-83-1	COD	2.41 g O2/g	Perio	d		14 days	
EC: 201-148-0	BOD5/COD	0.17	% Bio	odegradable	90 %		
butan-1-ol	BOD5	1.71 g O2/g	Conc	entration		Non-applicable	
CAS: 71-36-3	COD	2.46 g O2/g	Perio	d		19 days	
EC: 200-751-6	BOD5/COD	0.69	% Bio	odegradable		98 %	
Bioaccumulative potential:							
Ide	entification			Віоассі	umulatior	n potential	
4-methylpentan-2-one			BC	F	2		
CAS: 108-10-1			Po	w Log	1.31		
EC: 203-550-1			Por	tential	Low		
Xylene			BC	F	9		
CAS: 1330-20-7			Po	w Log	2.77		
EC: 215-535-7			Por	tential	Low		
2-methoxy-1-methylethyl acetate			BC	F	1		
CAS: 108-65-6			Po	w Log	0.43		
EC: 203-603-9		F		tential	Low		
1-methoxy-2-propanol			BC	F	3		
CAS: 107-98-2			Po	w Log	-0.44		
EC: 203-539-1			Por	tential	Low		
Formic acid			BCF		3		
CAS: 64-18-6			Por	w Log	-0.54		
EC: 200-579-1			Pot	Potential Lo		w	
2-methylpropan-1-ol			BC	F	3	3	
CAS: 78-83-1			Por	w Log	0.76		
EC: 201-148-0			Por	tential	Low		
butan-1-ol			BC	F	1		
CAS: 71-36-3			Por	w Log	0.88		
EC: 200-751-6			Por	tential	Low		
Mobility in soil:							
Identification	Abso	rption/desorption			Volati	ility	
4-methylpentan-2-one	Кос	Non-applicable		Henry		Non-applicable	
CAS: 108-10-1	Conclusion	Non-applicable		Dry soil		Non-applicable	
EC: 203-550-1	Surface tension	2,35E-2 N/m (2	25 ºC)	Moist soil		Non-applicable	

CAS: 108-10-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-550-1	Surface tension	2,35E-2 N/m (25 °C)	Moist soil	Non-applicable
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Formic acid	Кос	Non-applicable	Henry	Non-applicable
CAS: 64-18-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-579-1	Surface tension	3,862E-2 N/m (25 °C)	Moist soil	Non-applicable
2-methylpropan-1-ol	Кос	Non-applicable	Henry	Non-applicable
CAS: 78-83-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-148-0	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Non-applicable
butan-1-ol	Кос	2.44	Henry	5,39E-2 Pa·m ³ /mol
CAS: 71-36-3	Conclusion	Very High	Dry soil	Yes
EC: 200-751-6	Surface tension	2,567E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:



ON THE MARKET)

NEUTRALIZATOR RDZY - RUST CONVERTOR

ECTION 12: ECOLOGICAL INFORMATION (continued)

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 03 05*	organic wastes containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

1	14.1	UN number:	UN1263
1	14.2	UN proper shipping name:	PAINT RELATED MATERIAL
1	14.3	Transport hazard class(es):	3
$\langle \simeq \rangle$		Labels:	3
1	14.4	Packing group:	III
3 1	14.5	Environmental hazards:	No
1	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
1	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of dan	gero	us goods by sea:	
With regard to IMD)G 39	-18:	

With regard to IMDG 39-18:

** Changes with regards to the previous version



Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU (THIS SDS IS JUST FOR INFORMATIVE PURPOSE. THE SDS SHALL BE SUPPLIED IN AN OFFICIAL LANGUAGE OF THE COUNTRY WHERE THE PRODUCT IS PLACED ON THE MARKET)

NEUTRALIZATOR RDZY - RUST CONVERTOR

ECTION 14: TRANSPO	ORT I	INFORMATION ** (continued	1)
	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT RELATED MATERIAL
	14.3	Transport hazard class(es):	3
		Labels:	3
	14.4	Packing group:	III
3	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	163, 223, 367, 955
		EmS Codes:	F-E, S-E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Non-applicable
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of dar	ngero	us goods by air:	
With regard to IAT	TA/ICA	AO 2020:	
	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT RELATED MATERIAL
	14.3	Transport hazard class(es):	3
		Labels:	3
3	14.4	Packing group:	III
•	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Formic acid. Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Formic acid (Product-type 2, 3, 4, 5, 6) REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable Seveso III: Lower-tier Upper-tier Section Description reauirements requirements P5c FLAMMABLE LIQUIDS 5000 50000 Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc): Non-applicable Specific provisions in terms of protecting people or the environment: It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product. Other legislation:



NEUTRALIZATOR RDZY - RUST CONVERTOR

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

TRANSPORT INFORMATION (SECTION 14):

- UN number
- Packing group

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour

- H332: Harmful if inhaled
- H315: Causes skin irritation

H319: Causes serious eye irritation

H335: May cause respiratory irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Eye Dam. 1: H318 - Causes serious eye damage

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

- Flam. Lig. 3: H226 Flammable liquid and vapour
- Skin Corr. 1A: H314 Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Flam. Liq. 2: Calculation method (2.6.4.3) Acute Tox. 4: Calculation method Skin Irrit. 2: Calculation method Eye Irrit. 2: Calculation method STOT SE 3: Calculation method

Advice related to training:


Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:



NEUTRALIZATOR RDZY - RUST CONVERTOR

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOG-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.