

PREFILL SPRAY

TO SOLUTION OF THE PROPERTY OF

EAN code: 5907588400374 item no.: 001028 female

EAN code: 5907588403627 item no.: 0010281 PROFI female EAN code: 5907588407830 item no.: 0010282 PROFI PLUS female



PROPERTIES

The prefill spray is filled with gas and is ready for use after adding the colour of the desired shade. The 400 ml can can hold up to 100 ml of paint with a viscosity of up to 240s (DIN4/20°C). It can be used for almost any type of paint. Dilutes acrylic, alkyd and cellulose paints very well. Product efficiency: 1-2m² depending on the thickness of layer. The drying time depends on the type of paint used.

NOTE: The product is intended for single-component substances. Acrylic paint should be put through a sieve.



METHOD OF USE

Thoroughly clean, degrease, and then dry the surface. Cover adjacent areas with masking materials. Before use, shake the container well for about 3 minutes. When painting, keep the container at 15-20 cm distance from the surface. After use, invert the container and spray until the valve is empty.

Important: after filling the can with thick varnish, rinse the valve with 10 ml of solvent in the same way as when filling with varnish. Use a solvent in accordance with the recipe of a given mixing plant.



PHYSICAL PROPERTIES

density at 20°C: 0,722 g/cm³



STORAGE







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the package.



SAFETY

See Safety Data Sheet

PREFILL SPRAY Page - 1



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

PREFILL SPRAY Page - 2