



## PODKŁAD WYPEŁNIAJĄCY BIAŁY

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** PODKŁAD WYPEŁNIAJĄCY BIAŁY
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Sealant in aerosol.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna  
ul. Chemiczna 3  
65-713 Zielona Góra - Polska  
Phone.: 68 451 99 99 - Fax: 68 451 99 00  
technolog@boll.pl
- 1.4 Emergency telephone number:**

### SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aerosol 1: Flammable aerosols, Category 1, H222  
Aerosol 1: Pressurised container: May burst if heated., H229  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Eye Irrit. 2: Eye irritation, Category 2, H319  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Danger**



**Hazard statements:**

H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211: Do not spray on an open flame or other ignition source  
P251: Do not pierce or burn, even after use  
P271: Use only outdoors or in a well-ventilated area  
P273: Avoid release to the environment  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P403: Store in a well-ventilated place  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

**Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking  
EUH208: Contains Fatty acids, C18-unsatd., trimers, compds. with oleylamine. May produce an allergic reaction

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** active ingredient mixture with a propellant. Extruding gas: dimethyl ether

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	<b>Dimethyl ether<sup>(1)</sup></b> ATP CLP00	25 - <50 %
	Regulation 1272/2008 Flam. Gas 1: H220; Press. Gas: H280 - Danger	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	<b>2-butanone<sup>(1)</sup></b> ATP CLP00	10 - <25 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	<b>Acetone<sup>(1)</sup></b> ATP CLP00	10 - <25 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(1)</sup></b> ATP CLP00	2,5 - <10 %
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 7779-90-0 EC: 231-944-3 Index: Non-applicable REACH: 01-2119485044-40-XXXX	<b>trizinc bis(orthophosphate)<sup>(1)</sup></b> ATP CLP00	2,5 - <10 %
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	
CAS: 147900-93-4 EC: Non-applicable Index: Non-applicable REACH: 01-2119971821-33-XXXX	<b>Fatty acids, C18-unsatd., trimers, compds. with oleylamine<sup>(1)</sup></b> Self-classified	0,1 - <1 %
	Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Chronic 2: H411; Skin Sens. 1: H317; STOT RE 2: H373 - Warning	

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

- CONTINUED ON NEXT PAGE -



## PODKŁAD WYPEŁNIAJĄCY BIAŁY

### SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### **By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### **4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

#### **4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### **5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

#### **5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### **5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### **6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

#### **6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### **6.4 Reference to other sections:**

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### **7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 7: HANDLING AND STORAGE (continued)**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**B.- Technical recommendations for the prevention of fires and explosions**

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations to prevent ergonomic and toxicological risks**

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Technical measures for storage**

Minimum Temp.: 5 °C  
Maximum Temp.: 20 °C  
Maximum time: 24 Months

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
	IOELV (8h)	1000 ppm	1920 mg/m <sup>3</sup>
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)		
2-butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m <sup>3</sup>
	IOELV (STEL)	300 ppm	900 mg/m <sup>3</sup>
Acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>
	IOELV (STEL)		

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1879 - 1909 mg/m <sup>3</sup>	Non-applicable
2-butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1146 - 1176 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	585 - 615 mg/m <sup>3</sup>	Non-applicable
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	171 - 201 mg/kg	Non-applicable
	Inhalation	Non-applicable	2405 - 2435 mg/m <sup>3</sup>	1195 - 1225 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	945 - 975 mg/m <sup>3</sup>	945 - 975 mg/m <sup>3</sup>	465 - 495 mg/m <sup>3</sup>	465 - 495 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	68 - 98 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-10 - 20 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	456 - 486 mg/m <sup>3</sup>	Non-applicable
2-butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	16 - 46 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	397 - 427 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	91 - 121 mg/m <sup>3</sup>	Non-applicable
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	47 - 77 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	47 - 77 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	185 - 215 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	844,7 - 874,7 mg/m <sup>3</sup>	844,7 - 874,7 mg/m <sup>3</sup>	87,34 - 117,34 mg/m <sup>3</sup>	87,34 - 117,34 mg/m <sup>3</sup>
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	Oral	Non-applicable	Non-applicable	-14,17 - 15,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	68 - 98 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-12,5 - 17,5 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification					
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	145 - 175 mg/L	Fresh water	-14,85 - 15,16 mg/L	
	Soil	-14,96 - 15,05 mg/kg	Marine water	-14,98 - 15,02 mg/L	
	Intermittent	-13,45 - 16,55 mg/L	Sediment (Fresh water)	-14,32 - 15,68 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,93 - 15,07 mg/kg	
2-butanone CAS: 78-93-3 EC: 201-159-0	STP	694 - 724 mg/L	Fresh water	40,8 - 70,8 mg/L	
	Soil	7,5 - 37,5 mg/kg	Marine water	40,8 - 70,8 mg/L	
	Intermittent	40,8 - 70,8 mg/L	Sediment (Fresh water)	269,74 - 299,74 mg/kg	
	Oral	985 - 1015 g/kg	Sediment (Marine water)	269,7 - 299,7 mg/kg	
Acetone CAS: 67-64-1 EC: 200-662-2	STP	85 - 115 mg/L	Fresh water	-4,4 - 25,6 mg/L	
	Soil	14,5 - 44,5 mg/kg	Marine water	-13,94 - 16,06 mg/L	
	Intermittent	6 - 36 mg/L	Sediment (Fresh water)	15,4 - 45,4 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-11,96 - 18,04 mg/kg	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	20,6 - 50,6 mg/L	Fresh water	-14,82 - 15,18 mg/L	
	Soil	-14,91 - 15,09 mg/kg	Marine water	-14,98 - 15,02 mg/L	
	Intermittent	-14,64 - 15,36 mg/L	Sediment (Fresh water)	-14,02 - 15,98 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,9 - 15,1 mg/kg	
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	STP	-14,9 - 15,1 mg/L	Fresh water	-14,98 - 15,02 mg/L	
	Soil	20,6 - 50,6 mg/kg	Marine water	-14,99 - 15,01 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	102,8 - 132,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	41,5 - 71,5 mg/kg	

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

- CONTINUED ON NEXT PAGE -





**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	 CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	89,2 % weight
V.O.C. density at 20 °C:	663,4 kg/m <sup>3</sup> (663,4 g/L)
Average carbon number:	4
Average molecular weight:	75,25 g/mol

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	<input type="checkbox"/> White
Odour:	Characteristic
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	-24 °C
Vapour pressure at 20 °C:	520000 Pa
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	888 kg/m <sup>3</sup>
Relative density at 20 °C:	0,888
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

**Flammability:**

Flash Point:	-42 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	235 °C
Lower flammability limit:	1,8 % Volume
Upper flammability limit:	18,6 % Volume

**Explosive:**

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 10: STABILITY AND REACTIVITY (continued)**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- CONTINUED ON NEXT PAGE -





## PODKŁAD WYPEŁNIAJĄCY BIAŁY

### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

#### F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

#### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	308,5 mg/L (4 h)	Rat
2-butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: 147900-93-4 EC: Non-applicable	LD50 oral	1570 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
2-butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Species	Genus
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae
Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: 147900-93-4 EC: Non-applicable	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
2-butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O2/g	Concentration	Non-applicable
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
2-butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low
Acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable
2-butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
Acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT) /Aspiration Toxicity

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2017 and RID 2017:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Special regulations: 190, 327, 344, 625  
Tunnel restriction code: D  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 38-16:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Special regulations: 190, 277, 327, 344, 63, 959  
EmS Codes: F-D, S-U  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2018:

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500
E2		200	500

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Acetone. Product under the provisions of Article 9

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Non-applicable

**Texts of the legislative phrases mentioned in section 2:**

- CONTINUED ON NEXT PAGE -



**PODKŁAD WYPEŁNIAJĄCY BIAŁY**

**SECTION 16: OTHER INFORMATION (continued)**

H222: Extremely flammable aerosol  
H319: Causes serious eye irritation  
H336: May cause drowsiness or dizziness  
H411: Toxic to aquatic life with long lasting effects  
H229: Pressurised container: May burst if heated

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H302 - Harmful if swallowed  
Aquatic Acute 1: H400 - Very toxic to aquatic life  
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Flam. Gas 1: H220 - Extremely flammable gas  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Press. Gas: H280 - Contains gas under pressure, may explode if heated  
Skin Sens. 1: H317 - May cause an allergic skin reaction  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)  
STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

Aerosol 1: Calculation method  
Eye Irrit. 2: Calculation method  
STOT SE 3: Calculation method  
Aquatic Chronic 2: Calculation method  
Aerosol 1: Calculation method

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -