



PRIMER FILLER SPRAY

EAN code: 5907588407939 item no.: 001051 white
EAN code: 5907588407946 item no.: 001052 grey
EAN code: 5907588407953 item no.: 001053 black



PROPERTIES

Quick-drying acrylic primer with very good filling and anti-corrosive properties. Designed for the surface preparation in varnishing works, especially for leveling the surface of putty and old coatings. It has excellent adhesion to many different substrates and is easy to grind. It can be covered with most of available paints and varnishes.



COLOUR



white



grey



black



METHOD OF USE

Thoroughly clean, degrease and then dry the surface. Before applying the primer, we recommend to matt the surface and to clean and degrease it again. Cover adjacent areas with masking materials. Shake the container for about 3 minutes before use. When painting, keep the container at 15-20 cm distance from the surface. After about 1,5 hours the surface can be varnished. After use, invert the container and spray until the valve is empty.



SUBSTRATE

- **metal** - sand, blow and degrease with "BOLL silicone remover", and then apply another layer.
- **non-ferrous metals (zinc, aluminum, copper, etc.)** - grind, blow and degrease with "BOLL silicone remover", and then apply another layer.
- **reactive primer** - sand, blow, degrease with "BOLL silicone remover", and then apply another layer
- **epoxy primer** - can be used to isolate materials. After sanding, blow, degrease with "BOLL silicone remover", and then apply another layer.
- **two-component acrylic primer** - apply control powder or spray. After sanding with fine paper P400-P600 dry or P800-P1200 wet, blow, degrease with "BOLL silicone remover", and then apply another layer.
- **polyester putties** - sand, blow and degrease with "BOLL silicone remover", and then apply another layer.



APPLICATION



Thoroughly clean and roughen the surface



Thoroughly clean and degrease the surface



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Evaporation time between layers: 5 ÷ 10 minutes



After about 1,5 hours, the surface can be varnished



After use, invert the container and spray until the valve is empty



PHYSICAL PROPERTIES

density at 20°C:

0,888 g/cm³



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.