

TECHNICAL DATA SHEET

PRIMER FILLER SPRAY

EAN code: 5907588407953 item no.: 001053 black

EAN code: 5907588407946 item no.: 001052 grey

EAN code: 5907588407939 item no.: 001051 white



+ PROPERTIES

Quick-drying acrylic primer spray. The product offers excellent filling and anti-corrosive properties, making it ideal for surface preparation in painting and varnishing projects. It is specifically designed for leveling putty and old coatings, providing superb adhesion to a wide range of surfaces. Easy to sand, it can be coated with most available paints and varnishes.

• COLOUR



white



grey



black

= SURFACE

- **metal** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.
- **non-ferrous metals (zinc, aluminum, copper, etc.)** - prime, sand, blow off and degrease with "BOLL silicone remover", then apply another coat.
- **old paint coatings** - sand with P220 - P320, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- **epoxy primer** - can be used to isolate materials. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat.
- **two-component acrylic primer** - apply lacquer or powder control. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat.
- **polyester putty** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.



APPLICATION



Thoroughly clean and sand the surface with P240 - P360



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm



Time between layers: 5 – 10 minutes



After about 1.5 hours, the surface can be coated with varnish



After use, turn the container over and spray until the valve is empty



PHYSICAL PROPERTIES

Physical state:	aerosol
Temperature of use:	+15°C – +25°C



STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



SHELF LIFE

Two years from the production date placed on the package.

! SAFETY

See Safety data Sheet.

☰ OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.