

## TECHNICAL DATA SHEET

### PRIMER FILLER SPRAY

**EAN code:** 5907588407953 item no.: 001053 black

**EAN code:** 5907588407946 item no.: 001052 grey

**EAN code:** 5907588407939 item no.: 001051 white



#### + PROPERTIES

Quick-drying acrylic primer spray. The product offers excellent filling and anti-corrosive properties, making it ideal for surface preparation in painting and varnishing projects. It is specifically designed for leveling putty and old coatings, providing superb adhesion to a wide range of surfaces. Easy to sand, it can be coated with most available paints and varnishes.

#### • COLOUR



white



grey



black

#### = SURFACE

- |                                                               |                                                                                                                                |
|---------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| • <b>metal</b>                                                | - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.                                        |
| • <b>non-ferrous metals</b><br>(zinc, aluminum, copper, etc.) | - prime, sand, blow off and degrease with "BOLL silicone remover", then apply another coat.                                    |
| • <b>old paint coatings</b>                                   | - sand with P220 - P320, blow off, degrease with "BOLL Silicon remover", and then apply another coat.                          |
| • <b>epoxy primer</b>                                         | - can be used to isolate materials. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat. |
| • <b>two-component acrylic primer</b>                         | - apply lacquer or powder control. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat.  |
| • <b>polyester putty</b>                                      | - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.                                        |



## APPLICATION



Thoroughly clean and sand the surface with P240 - P360



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm



Time between layers: 5 – 10 minutes



After about 1.5 hours, the surface can be coated with varnish



After use, turn the container over and spray until the valve is empty



## PHYSICAL PROPERTIES

Physical state:	aerosol
Temperature of use:	+15°C – +25°C



## STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



## SHELF LIFE

Two years from the production date placed on the package.

**! SAFETY**

See Safety data Sheet.

**☰ OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.