



## MASKING TAPE 60°C



EAN code: 5907588408851 item no.: 0040051 type 19mm/50m  
EAN code: 5907588408875 item no.: 0040052 type 25mm/50m  
EAN code: 5907588408899 item no.: 0040053 type 30mm/50m  
EAN code: 5907588408912 item no.: 0040054 type 38mm/50m  
EAN code: 5907588408936 item no.: 0040055 type 50mm/50m

**+** PROPERTIES

High quality paper tape for paint jobs. It adheres well to a variety of surfaces and leaves no residue after the drying process.

Available in rolls of 50 m in length and widths: 19, 25, 30, 38 and 50 mm

**•••** COLOUR

○ white

**☞** METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dust-free and degreased.

**⊕** PHYSICAL PROPERTIES

description:	heat resistant paper masking tape, saturated crepe paper
binder :	natural rubber
temperature resistance:	1h/60°C
total thickness :	130 µm
adhesion to steel :	6,0 N/25 mm
tensile strength:	85 N/25 mm
total elongation :	7 %
ROLLING BALL TACK test :	2cm

**🏠** STORAGE CONDITIONS

Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



## SHELF LIFE

Stored in a dry place at 18 - 21°C, the tape retains its properties for 12 months.



## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.