

**CLEAR COAT MS 2:1**

EAN code: 5907588409063 item no.: 001660

EAN code: 5907588409070 item no.: 001661 hardener STANDARD

EAN code: 5907588410106 item no.: 0016611 hardener FAST

**PROPERTIES**

Clear coat MS class (MediumSolid). It has a very good flow and provides a high gloss. Thanks to the use of modern resins, the obtained coating is resistant to scratches, UV and weather conditions. It does not require the use of a thinner during application.

**COLOUR**








colorless

**SURFACE**

Can be applied over most commercially available thinner and waterborne basecoats.



## APPLICATION

	Mixing ratio:	by volume		by mass	
	clear coat	2		100g	
	hardener STANDARD	1		52g	
	hardener FAST	1		48,5g	
	Viscosity: DIN 4 20°C 15 - 17 s				
	Mixture life				
	hardener STANDARD	hardener FAST			
	20°C      4 h	20°C	3,5h		
	Nozzle	1,2 - 1,3 mm			
	Pressure	1,2 – 2,5 bar			
	Number of layers	2 layers			
	Evaporation time 5 - 10 min				
		20°C		60°C	
		STANDARD	FAST	STANDARD	FAST
	Dust free	30 min	20 min	5 min	5 min
	Operating hardness	12 h	9 h	30 min + 2h/20°C	20 min + 2h/20°C
	Overall hardness	36 h	28 h	30 min + 24h/20°C	20 min + 2h/20°C
	Short waves				
	max 90°C				
	8 - 12 min				



## STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



## SHELF LIFE

24 months from the date of production placed on the package.



## SAFETY

See Safety Data Sheet.



## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.