



QUICK-DRYING PRIMING PAINT SPRAY

EAN code: 5907588407922 item no.: 0010210 white
EAN code: 5907588402545 item no.: 001020 beige
EAN code: 5907588410007 item no.: 001021 grey
EAN code: 5907588403641 item no.: 0010199 black



+ PROPERTIES

Quick drying primer in an aerosol is perfect for preparing the ground in painting car body parts. It has excellent rust protection properties and is very scratch resistant, making it a very good substrate before applying paint. Easy to work with, no clogging of sandpaper. Can be coated with acrylic, alkyd, cellulose and epoxy paints.

• COLOUR

○ white ● beige ● grey ● black

☞ METHOD OF USE

Thoroughly clean and degrease and then dry the areas to be covered with paint. Before applying the primer, it is recommended to matt the surface and to clean and degrease it again. Cover adhering surfaces with paper. Shake the container well for about 3 minutes before use. When painting, keep the container at a distance of 15-20 cm from the surface to be coated. After about 1 hour the surface can be varnished. After use, invert the container and spray until the valve is empty.

☰ PODŁOŻA

- **metal** - sand, blow off and degrease with "BOLL silicone remover", and then apply another layer.

- **non-ferrous metals (zinc, aluminum, copper, etc.)** - grind, blow off and degrease with "BOLL silicone remover", and then apply another layer.

- **reactive primer** - sand, blow off, degrease with "BOLL silicone remover", and then apply another layer

- **epoxy primer** - can be used to isolate materials. After sanding, blow off, degrease with "BOLL silicone remover", and then apply another layer.

- **two-component acrylic primer** - apply varnish or control powder. After sanding with fine paper, dry with P400-P600 or wet with P800-P1200, blow off, degrease with "BOLL silicone remover", and then apply another layer.

- **polyester putties** - sand, blow off and degrease with "BOLL silicone remover", and then apply another layer.



APPLICATION



Thoroughly clean the surface and roughen it



Thoroughly clean the surface and degrease it



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Flash off time between layers: 5 ÷ 10 minutes



After about 1 hour, the surface can be covered with varnish



After use, invert the container and spray until the valve is empty



PHYSICAL PROPERTIES

boiling point:	-24°C
flash point:	215°C
solvents:	aliphatic hydrocarbons
density at 20°C:	0,727 g/cm ³
flammability limit:	upper: 18,6 % vol. / lower: 1,1 % vol.
organic solvetns:	98,2%



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the date of production placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.