

### **INSIDE COATING SPRAY**

BOLL SOLL PROPERTY AND THE PROPERTY AND



EAN code: 5907588402989 item no.: 0010102 white EAN code: 5907588410014 item no.: 001010 amber



#### **PROPERTIES**

The preservative for closed profiles (such as doors, bonnet, thresholds, etc.) is a wax-based agent which forms a flexible layer protecting against water, salt and rust. It is very efficient, semi-transparent in white or amber shade.



### **COLOUR**



white



amber



### **METHOD OF USE**

Inside coating spray should be injected into existing holes in the car body using a tube included in the set. You can drill additional 6 mm diameter holes, If necessary. Shake the container well for about 3 minutes before use. After use, invert the container and spray until the valve is empty.



## **APPLICATION**



Mix thoroughly



Apply to existing holes in the car body with the attached tube



Recommended coating thicknesses from 0. 2mm to 0. 4mm



Drying time approx. 4-5 hours at 20°C



After use, invert the container and spray until the valve is empty

INSIDE COATING SPRAY Page - 1



## **PHYSICAL PROPERTIES**

physical state: aerosol density (at 20°C): 0,667 g/cm<sup>3</sup>



# STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



## **SHELF LIFE**

Two years from the production date on the packaging.



### **SAFETY**

See Safety Data Sheet.



## **OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

INSIDE COATING SPRAY Page - 2