

TECHNICAL DATA SHEET

THERMAL LACQUER 800°C SPRAY

EAN code: 5907588400008 item no.: 001018 silver **EAN code:** 5907588410021 item no.: 001019 black



+

PROPERTIES

A specialized coating designed for painting elements exposed to extremely high temperatures. The product features exceptional thermal resistance (up to +800°C), remarkable durability, and excellent coverage. Thanks to its unique silicone resin-based formula, BOLL thermal lacquer is ideal for coating elements such as exhaust system parts (e.g., mufflers, exhaust pipes, and mounting components), exhaust manifolds, fireplace elements, and outdoor grills.





APPLICATION



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm



Time between layers: 5 – 10 minutes



Drying time 1 hour at 20°C



After use, turn the container over and spray until the valve is empty



#

PHYSICAL PROPERTIES

Physical state::

Temperature of use:

aerosol

+18°C - +25°C

6

STORAGE







Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

幽

SHELF LIFE

Two years from the production date placed on the package.

1

SAFETY

See Safety data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.