

TECHNICAL DATA SHEET

MACHINE GREASE TOWOT



EAN code: 5907588412186 item no.: 001070 jar 500g

+ PROPERTIES

Grease for lubricating sliding bearings and other friction surfaces operating under light to moderate loads, especially in humid environments. Offers good water resistance and corrosion protection. Recommended for older machines and equipment.

Specyfication: DIN 51502: K2C-20, ISO 6743/9: ISO L-XBAHA2

• COLOUR



☰ APPLICATIONS

- industry, agriculture, automotive
- sliding bearings under low to moderate loads
- threaded connections, pins, bolts, guides, gears, steel cables

⚙ PHYSICAL PROPERTIES

Physical state:	plastic grease
Temperature of use:	-20°C – +60°C
Operating temperature:	-20°C – +60°C
NLGI class:	2
Drip temperature:	98°C
Type of thickener:	calcium soap
Base oil viscosity:	150 mm ² /s



STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



SHELF LIFE

36 months from the production date placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.