

TECHNICAL DATA SHEET

ACRYLIC LACQUER FOR WHEELS RALLY SPRAY

EAN code: 5907588490009 item no.: 001013 silver metallic

EAN code: 5907588413015 item no.: 0010136 gold metallic

EAN code: 5907588413114 item no.: 0010137 black metallic



+ PROPERTIES

A durable and aesthetic paint designed for the refurbishment and styling of steel and aluminium wheels. It features very good hiding power and resistance to mechanical damage, road chemicals, and weather conditions. It forms a smooth, uniform coating, restoring a fresh and attractive appearance to the wheels. Available in black with a matte or gloss finish, as well as in three metallic variants: black, gold and silver.

NOTE: It is recommended to use a primer before applying the lacquer.

When applying the gold color, it is recommended to use a white primer.

• COLOUR



silver metallic



gold metallic



black metallic

/// APPLICATION



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm

NOTE: It is recommended to use a primer before applying the lacquer.

When applying the gold color, it is recommended to use a white primer.



Time between layers: 5 – 10 minutes



Drying time 1,5 hours at 20°C



After use, turn the container over and spray until the valve is empty

**PHYSICAL PROPERTIES**

Physical state: aerosol
Temperature of use: +18°C – +25°C

**STORAGE**

Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

**SHELF LIFE**

Two years from the date placed on the package.

**SAFETY**

See Safety Data Sheet.

**OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.