



POLYBUTENE SEALANT FOR WINDSCREENS

EAN code: 5907588440004 item no.: 007010 cap. 310ml




PROPERTIES

The sealant for car windows is a one-component, permanently plastic sealant based on butylene, which exhibits excellent adhesion on all dry and degreased surfaces. It is not soluble in water, does not harden at low temperatures and does not become liquid at elevated temperatures. It does not shrink and is resistant to sunlight and oxidation. It is perfect for sealing windows placed in rubber profiles in cars and buses. It is covered with a smooth, elastic skin and thanks to its impermeability and resistance to high and low temperatures, it prevents water and dust from entering the interior of the vehicle



COLOUR

 black



METHOD OF USE


Dirt should be carefully removed and the places where the mass will be used should be degreased. Then, pierce the membrane in the thread, cut the nozzle according to the required cross-section and press the mass into the previously prepared places using a manual or pneumatic squeezer.



APPLICATION



Thoroughly clean the surface and degrease it



Apply with a BOLL squeezer



PHYSICAL PROPERTIES

consistency after hardening:	permanently plastic and intrinsically tacky
skinning:	< 48h (at 23°C and 55% RH)
density (at 20°C):	1.67 g/cm ³
thermal resistance after hardening:	-20 to + 75°C



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

Placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.