

INSIDE COATING

SKODEL DO SKODEL DO SKODEL DO SKODEL DE SKODEL

EAN: 5907588402972 item no.: 0010101 white EAN: 5907588470018 item no.: 001009 amber



PROPERTIES

The preservative for closed profiles (such as doors, bonnet, thresholds, etc.) is a wax-based agent which forms a flexible protective layer perfectly protecting against water, salt and rust. It is very efficient, transparent in an amber shade after use.



COLOUR



white



amber



METHOD OF USE

The agent should be injected into existing holes in the car body using a spray gun equipped with a suitable adapter. If necessary, drill holes 6 mm in diameter. Shake the container well for about 3 minutes before use. Excess of the preparation can be removed with white spirit.



APPLICATION



Mix thoroughly



Inject into existing holes in the car body using a spray gun at a pressure of 3-6 bar equipped with a suitable adapter



Drying time about 4 hours

INSIDE COATING Page - 1



PHYSICAL PROPERTIES

0,86 g/cm³ density (at 20°C): boiling point: 142°C flash point: 21-55°C

flammability limits: upper: 7,5 % vol / lower: 0,6 % vol.



EQUIPMENT CLEANING

Wash the gun with white spirit.



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

Two years from the date of production on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

INSIDE COATING Page - 2