

TECHNICAL DATA SHEET

BRUSHABLE ONE-COMPONENT SEALANT



EAN code: 5907588490016 item no.: 007001 cont. 1kg

+ PROPERTIES

Brushable sealant is a one-component rubber-based sealant that hardens at room temperature through evaporation of solvents. It forms a strong and resistant seal, does not form cracks and guarantees optimum adhesion on substrates such as raw or primed metals. It prevents the entry of water, dust or dirt. It is used in the manufacture and repair of automobile bodies to seal welds, seams, sheet metal soldered, bolted and overlapped joints, while creating a seal with the same characteristics as the original.

• COLOUR



grey

⤿ METHOD OF USE

Optimum application temperature: from +15°C to +35°C. Apply directly to metal.

/// APPLICATION



Thoroughly clean the surface of possible rust



Thoroughly clean and degrease the surface with "BOLL Silicon remover"



Apply with a BOLL sealing compound brush



Curing time: 24 hours at 20°C



Can be painted wet-on-wet



Can be painted with all paint systems



PHYSICAL PROPERTIES

Density at 20°C:	1,20 g/cm ³
Peel formation time:	approx. 30 minutes at 23°C
Curing time:	24 hours (1mm thick layer)
Shore A hardness:	approx. 70
Tearing resistance:	13 N/mm
Temperature resistance:	from -20°C to +60°C
Water resistance:	good
Oil resistance:	medium
Solvent resistance:	medium
UV resistance:	good



CLEANING

The brush should be washed with turpentine.



STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



SHELF LIFE

Placed on the package.



SAFETY

See Safety Data Sheet.

**OTHER INFORMATION**

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.